


CX2072NL

- BALUN TRANSFORMER, 1:1
- 10-1000 MHz
- IMPEDANCE = 75 OHMS
- SURFACE MOUNT

NOTES: UNLESS OTHERWISE SPECIFIED

1. OPERATING TEMPERATURE: -40°C TO +85°C
2. STORAGE TEMPERATURE: -50°C TO +125°C
3. JEDEC MOISTURE: LEVEL 1
4. DIMENSIONS ARE IN MM/[IN] WITH THE FOLLOWING TOLERANCE:
.X = ±0.1 [±.004]
.XX = ±0.05 [±.002]
5. OPTIONAL TAPE & REEL PACKAGING CAN BE ORDERED BY ADDING A "T" SUFFIX TO THE PART NUMBER; ie: CX2072NLT.
6. ROHS COMPLIANT



ELECTRICAL SPECIFICATIONS: @ 25° C


INSERTION LOSS;

FREQUENCY	ATTENUATION
10 MHz	-1.0 dB MAX
50 MHz	-0.5 dB MAX
150 MHz	-0.5 dB MAX
300 MHz	-0.5 dB MAX
450 MHz	-0.5 dB MAX
600 MHz	-0.5 dB MAX
870 MHz	-0.6 dB MAX
1000 MHz	-0.7 dB MAX

RETURN LOSS:

FREQUENCY	ATTENUATION
10 MHz	-20.0 dB MIN
50 MHz	-20.0 dB MIN
150 MHz	-20.0 dB MIN
300 MHz	-20.0 dB MIN
450 MHz	-20.0 dB MIN
600 MHz	-20.0 dB MIN
870 MHz	-20.0 dB MIN
1000 MHz	-16.0 dB MIN

MECHANICAL SPECIFICATIONS:



© Copyright, 2013. Pulse Electronics Corp. All rights reserved. Drawing specifications subject to change without notice. (12/16/13)

PULSE CONFIDENTIAL
&
PROPRIETARY

PRODUCT SPECIFICATION:
XFMR, RF, 1:1, XMSN, KAYAK8, 10-1000MHZ

DWG. NO./ PART NO.
CX2072NL

SHEET:
1 OF 1

REV.
M10