

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	14APR2015	DW	CW
	B	ECR-15-018270	10DEC2015	DW	CW

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 50V  
RATED CURRENT: 5A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 0.8KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
OPERATION TEMPERATURE:  $-40\sim+125^{\circ}C$   
WIRE RANGE: 0.08~0.52 mm<sup>2</sup> (28~20 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20700X20XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 50V  
额定电流: 5A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 0.8KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
工作温度:  $-40\sim+125^{\circ}C$   
接线范围: 0.08~0.52 mm<sup>2</sup> (28~20 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20700X20XX000)

HMN-025-F 26-50	T2111502201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	13APR2015	TE Connectivity	NAME	HMN-025-F 26-50	
DIMENSIONS:		CHK	13APR2015				
mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD	13APR2015				
	0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-	PRODUCT SPEC	108-137122				
MATERIAL	FINISH	APPLICATION SPEC	114-137122	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
-	-	WEIGHT	-	A3	00779	T2111502201000	-
Customer Drawing				SCALE	3:2	SHEET	1 OF 1
						REV	B

1470-19 (3/13)