

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	14APR2015	DW	CW
	B	ECR-15-018270	10DEC2015	DW	CW

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 50V  
RATED CURRENT: 5A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 0.8KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
OPERATION TEMPERATURE:  $-40\sim+125^{\circ}C$   
WIRE RANGE:  $0.08\sim 0.52\text{ mm}^2$  (28~20 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20700X20XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 50V  
额定电流: 5A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 0.8KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
工作温度:  $-40\sim+125^{\circ}C$   
接线范围:  $0.08\sim 0.52\text{ mm}^2$  (28~20 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20700X20XX000)

HMN-025-F 26-50	T2111502201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC $\pm$
	1 PLC $\pm$
	2 PLC $\pm$
	3 PLC $\pm$
	4 PLC $\pm$
	ANGLES $\pm$
MATERIAL	FINISH
-	-
-	-

DWN	13APR2015
David Wang	
CHK	13APR2015
Chris Wang	
APVD	13APR2015
Xiang Xu	
PRODUCT SPEC	108-137122
APPLICATION SPEC	114-137122
WEIGHT	-
Customer Drawing	

		TE Connectivity	
NAME		HMN-025-F 26-50	
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	©-T2111502201000	-
SCALE		SHEET	REV
3:2		1 OF 1	B

1470-19 (3/13)