

NOTES: UNLESS OTHERWISE SPECIFIED.



1. MATERIAL AND FINISH:
1.1 BODY & COUPLING NUT: GOLD PLATED BRASS
1.2 CONTACT: GOLD PLATED BERYLLIUM COPPER
1.3 INSULATOR: PTFE (TEFLON)
1.4 COUPLING SPRING: BERYLLIUM COPPER UNPLATED
2. ELECTRICAL SPECIFICATIONS:
2.1 IMPEDANCE: 50 OHMS
2.2 FREQUENCY: 0 - 26.5 GHz
2.3 VSWR: 1.05+.02F(GHz) MAX AT 0-18 GHz, <1.50 TYPICAL AT 18-26.5 GHz
2.4 WORKING VOLTAGE: 170 VRMS MAX AT SEA LEVEL
2.5 DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS MIN AT SEA LEVEL
2.6 INSULATION RESISTANCE: 1000 MEGOHMS MIN
2.7 CONTACT RESISTANCE:
 CENTER CONTACT: INTIAL 3.0 MILLIOHM MAX,
 AFTER ENVIRONMENTAL 4.0 MILLIOHM MAX
 OUTER CONDUCTOR: INITIAL 2.0 MILLIOHM MAX,
 AFTER ENVIRONMENTAL - N/A
2.8 CORONA LEVEL: 125 VOLTS MIN AT 70,000 FEET
2.9 RF HIGH POTENTIAL WITHSTANDING VOLTAGE: 335 VRMS AT 4 & 7 MHz
3. MECHANICAL SPECIFICATIONS:
3.1 ENGAGE/DISENGAGE TORQUE: 2 INCH-POUNDS MAX
3.2 MATING TORQUE: 7-10 INCH-POUNDS WHEN BODY SUPPORTED WITH WRENCH
 8* INCH POUNDS MAX UNSUPPORTED
3.3 CONTACT RETENTION FORCE: 6 LBS MIN AXIAL FORCE ON MATING END
 4 IN-OZ MIN RADIAL TORQUE
3.4 DURABILITY: 500 CYCLES MIN
4. ENVIRONMENTAL:
(MEETS OR EXCEEDS THE APPLICABLE PARAGRAPH OF MIL-PRF-39012)
4.1 THERMAL SHOCK: MIL-STD-202, METHOD 107, CONDITION B,
 EXCEPT 115°C HIGH TEMP
4.2 OPERATING TEMPERATURE: -65°C TO 165°C
4.3 CORROSION: MIL-STD-202, METHOD 101, CONDITION B
4.4 SHOCK: MIL-STD-202, METHOD 213, CONDITION I
4.5 VIBRATION: MIL-STD-202, METHOD 204, CONDITION D
4.6 MOISTURE RESISTANCE: MIL-STD-202, METHOD 106

5. ALL HOLES PLATED THRU ENTIRE CIRCUIT BOARD STACKUP.


6. HOLE PATTERNS SYMMETRICAL ABOUT CENTER CPW TRACE.

7. FOR OPTIMUM CIRCUIT BOARD HIGH FREQUENCY PERFORMANCE:
7.1 MAINTAIN SOLID GROUND PLANE BELOW HF SUBSTRATE.
7.2 CONTROL PULLBACK OF TRACE AND GROUND FROM BOARD EDGE.
7.3 CONTINUE GROUNDED COPLANAR LINE BEYOND GROUND PADS.
7.4 PLACE 16 MIL DIA GROUND VIAS ON BOTH SIDE OF COPLANAR
 WAVEGUIDE LINE AT 50 MIL INTERVALS ALONG ENTIRE LENGTH.
7.5 IMMERSION GOLD PLATE (ENIG) ALL CONDUCTORS PER IPC-4552.

8. REFERENCE DIMENSIONS FOR 50 OHM GROUNDED CPW LINE, USING
ROGERS R04003, 8 MIL HIGH FREQUENCY CIRCUIT BOARD SUBSTRATE:
TRACE WIDTH: 15.5 MILS
GROUND GAPS: 10 MILS
CONDUCTOR THICKNESS: 1.4 MIL (INCLUDES PLATING)



MOUNTING FOOTPRINT
(TOP VIEW, INCLUDING TRACE DIMENSIONS)



 THE PROPRIETARY DOCUMENT IS PROPERTY OF CINCH CONNECTIVITY SOLUTIONS. IT IS CONFIDENTIAL IN NATURE, NON-TRANSFERABLE, AND ISSUED WITH THE UNDERSTANDING THAT IT IS NOT TO BE REPRODUCED OR COPIED WITHOUT PERMISSION AND IS RETURNABLE UPON DEMAND. INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009	3RD ANGLE PROJECTION		JOHNSON	
	RoHS2 ☒ 2011/65/EU		Title: PLUG ASSEMBLY, HIGH FREQ END LAUNCH, SMA, .010 MIL PIN	
	UNLESS OTHERWISE SPECIFIED UNITS: INCH		Model No. 142-0861-851	
	Size B	DO NOT SCALE DRAWING	Date: 11/3/2014	Sheet 1 of 1