

CATALOG LISTING

1EN330-R3

PAGE 1 OF 1

RELEASE NO. PR-22923

REPLACES

ISSUE

2

CHECK

REVISIONS

A PR22923

T S M

2 SEP 97

CHECK

CHECK



DDM/CAD

DRAWN

T S M

2 SEP 97

CHECK



- NOTES
- 1 - ENCLOSURE FINISHED WITH GREEN EPOXY BASED ENAMEL COLOR NO. 34151 PER FEDERAL STANDARD 595
 - 2 - SWITCH SEALED PER MIL-S-8805 SYMBOL 4
 - 3 - CIRCUIT DIAGRAM, CATALOG LISTING AND DATE CODE ARE SHOWN ON NAMEPLATE
 - 4 - COINCIDENCE OF OPERATING AND RELEASING POINTS:
.010 INCH OF PLUNGER TRAVEL
 - 5 - HARDWARE MAY BE PACKAGED UNASSEMBLED PER MIL-S-8805
 - 6 - GOLD CONTACT BASIC SWITCHES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH				THIRD ANGLE PROJECTION	
CHARACTERISTICS		ELECTRICAL DATA		SCALE FULL	
OPERATING FORCE — — — — — 6-12 LB		CONTACT ARRANGEMENT (6)		DO NOT SCALE PRINT	
FULL OVERTRAVEL — — — — — 30 LB MAX		2X S P D T		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
RELEASE FORCE — — — — — 4 LB MIN		28 VDC		ONE PLACE (.0) ±.030	
PRETRAVEL — — — — — .040 MAX		SEA LEVEL		TWO PLACE (.00) ±.015	
DIFFERENTIAL TRAVEL — — .020 MAX		50,000 FT.		THREE PLACE (.000) ±.005	
OVERTRAVEL — — — — — .250 MIN				ANGLES ±	
				WEIGHT 7.0 OZ MAX	

ANSI Y14.5M-1982 APPLIES