



- 1 CONTACTS: 0.00076[0.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[0.000150] MIN TIN ON SOLDER TAILS, ALL OVER 0.00127[0.000050] MINIMUM NICKEL
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- 3. DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- 5. ASSEMBLY KEYED FOR 5 VOLT CARDS
- 6. ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V)
- 7. RECESSED AMP AND CSA LOGOS LOCATED ON BOTH SIDES OF HOUSING.
- 8. MATERIAL: HOUSING & ORGANIZER; LCP, COLOR; BLACK CONTACTS; BRASS

6	1,17,34	ALL	36,67	5535653-2
	35,51,68	OTHER PINS		
5	1,17,34	ALL	36,67	5535653-1
	35,51,68	OTHER PINS		
VOLTAGE KEYING & IDENTIFICATION	5.0 [0.197]	4.25 [0.167]	3.5 [0.138]	PART NUMBER
	"L" (PIN LENGTH) AND LOCATION			
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L VARELA - DOCKS 03-23-05		STE TE Connectivity
DIMENSIONS: mm(INCHES)		D.L. GORENC 03-23-05		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. WALMSLEY 03-23-05		PIN HEADER ASSY, 68 POSN, TOP BOARD MTG, THRU-HOLE, AMP MEMORY CARD
0 PLC ±		PRODUCT SPEC		
1 PLC ±		APPLICATION SPEC		SIZE CAGE CODE DRAWING NO
2 PLC ± 0.13 [005]		WEIGHT 7.3 GRAMS		
3 PLC ±		CUSTOMER DRAWING		SCALE 4:1 SHEET 1 OF 1 REV P
4 PLC ±				
ANGLES ±				
FINISH 1				

**COPYRIGHT 2005  
TE CONNECTIVITY CORP  
ALL RIGHTS RESERVED**