

270 Series

Vitreous Enamel Power



Select 270 Type fixed resistors for applications requiring wattage ratings from 12 to 1000 watts. The 270 Type resistors are equipped with lug terminals suitable for soldering or sturdy bolt connection. When secure mounting is required, the hollow core of these resistors permit fastening with spring-type brackets, thru bolts or thru bolts with slotted-steel brackets.

Suitable for rugged applications, the 270 Type resistors feature all-welded construction and durable lead free vitreous enamel coating. Mounting brackets not included with resistors.

FEATURES

- Terminals suitable for soldering or bolt connection
- High wattage applications
- Rugged lead free vitreous enamel coating
- Flame resistant coating
- All-welded construction
- RoHS compliant available
- “Fast on” option – see terminal 538, <https://www.ohmite.com/assets/docs/terminals.pdf>

SERIES SPECIFICATIONS

Series	Wattage	Ohms	Core Code	Voltage	Std. Terminal
L12	12	0.1-51K	D	565	57
L25	25	0.15-100K	K	625	40
L50	50	0.38-260K	K	1625	40
L100	100	0.23-101K	M	2845	40
L175	175	0.13-101K	P	3595	46
L225	225	0.16-129K	P	4595	46
L500	500	0.38-218K	S	4970	45
L1000	1000	0.69-392K	S	8900	45

Non-Inductive versions available; Other sizes available; Also available in low cost Centohm or Silicone coating; Consult Ohmite.

* Maximum Voltage is based on Ohm's Law $[V=\sqrt{P \cdot R}]$ as limited by the resistance value of specified product

CHARACTERISTICS

Coating	Lead free vitreous enamel. Large models (500 watts and up) are supplied in Silicone Ceramic. Also available in low-cost Centohm coating; Consult factory.										
Core	Tubular ceramic.										
Terminals	Solder coated radial lug. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu										
Derating	Linearly from 100% @ +25°C to 0% @ +350°C.										
Tolerance	±5% 1Ω and over (J); ±10% under 1Ω (K)										
Power rating	Based on 25°C free air rating.										
Overload	10 times rated wattage for 5 seconds.										
Temperature coefficient	1 to 20Ω: ±400 ppm/°C; Above 20Ω: ±260 ppm/°C										
Dielectric withstanding voltage	1000 VAC: 12 to 100 watt rating. 3000 VAC: 175 to 225 watt rating (Measured from terminal to mounting bracket)										
Max. amps	use the formula $\sqrt{P/R}$										
Power limitations for high resistance values	When resistance exceeds the resistance values listed, derate the Power Rating by 25% to improve reliability. <i>No power derating necessary for ratings higher than 100W.</i>										
	<table> <tr> <th>Power rating</th><th>Resistance value</th></tr> <tr> <td>12W</td><td>3,900Ω</td></tr> <tr> <td>25W</td><td>12,000Ω</td></tr> <tr> <td>50W</td><td>35,000Ω</td></tr> <tr> <td>100W</td><td>75,000Ω</td></tr> </table>	Power rating	Resistance value	12W	3,900Ω	25W	12,000Ω	50W	35,000Ω	100W	75,000Ω
Power rating	Resistance value										
12W	3,900Ω										
25W	12,000Ω										
50W	35,000Ω										
100W	75,000Ω										
Mounting Hardware	see https://www.ohmite.com/assets/docs/hardware_resistor.pdf										

(continued)

270 Series

Vitreous Enamel Power

DIMENSIONS

in./mm



Series	Wattage	L		D		C	Core Code*	Std. Term.**
L12	12	1.75	44.4	0.313	7.94	0.188 / 4.76	D	57
L25	25	2.0	50.8	0.562	14.3	0.313 / 7.94	K	40
L50	50	4.0	101.6	0.562	14.3	0.313 / 7.94	K	40
L100	100	6.5	165.1	0.750	19.1	0.50 / 12.7	M	40
L175	175	8.5	215.9	1.125	28.6	0.75 / 19.1	P	46
L225	225	10.5	266.7	1.125	28.6	0.75 / 19.1	P	46
L500	500	12.0	304.8	2.50	63.5	1.75 / 44.5	S	45
L1000	1000	20.0	508.0	2.50	63.5	1.75 / 44.5	S	45

* <https://www.ohmite.com/assets/docs/200-210-270-custom.pdf>

** <https://www.ohmite.com/assets/docs/terminals.pdf>

ORDERING INFORMATION

Standard

F = Fast on (optional)	Non-inductive Blank = Standard N = Non-inductive	RoHS Compliant
L	25	J 100 E
Coating Blank = Vitreous C = Centohm S = Silicone	Series Wattage Tolerance J = 5% K = 10%	Ohms 1R0 = 1Ω 250 = 250Ω 1K0 = 1,000Ω 25K = 25,000Ω 25K5 = 25,500Ω

Made-to-order

Non-inductive Blank = Standard N = Non-inductive	Core Diameter See "Core and Terminal Selection"	RoHS Compliant
270	50	K 40 5 R 00 J E
Coating 270 = Vitreous 470 = Silicone Ceramic	Wattage Terminal Type See "Resistor Terminals for Tubular Cores"	Ohms R500 = 0.500Ω 1R00 = 1Ω 250R = 250Ω 1K00 = 1,000Ω 25K0 = 25,000Ω 25K5 = 25,500Ω

See website for custom core and terminal info

Standard part numbers for 270 series

Ohmic value		12 Watt		Ohmic value		12 Watt		Wattage		Ohmic value		Wattage		Ohmic value		Wattage	
value	Part No.	value	Part No.	value	Part No.	value	Part No.	value	Part No.	value	Part No.	value	Part No.	value	Part No.	value	Part No.
0.51	✓ L12JKR51E	180	✓ L12J180E	1	✓ L12J1R0E	270	✓ L12J270E	25	✓ L25J	2,500	✓ L25J	25	✓ L25J	3,000	✓ L30J	50	✓ L50J
1	✓ L12J1R0E	330	✓ L12J330E	3.3	✓ L12J3R3E	390	✓ L12J390E	50	✓ L50J	3,500	✓ L35J	50	✓ L50J	4,000	✓ L40J	100	✓ L100J
3.3	✓ L12J3R3E	470	✓ L12J470E	4.7	✓ L12J4R7E	560	✓ L12J560E	100	✓ L100J	4,000	✓ L40J	100	✓ L100J	5,000	✓ L50J	175	✓ L175J
10	✓ L12J10RE	1000	✓ L12J1K0E	10	✓ L12J10RE	1200	✓ L12J1K2E	175	✓ L175J	5,000	✓ L50J	175	✓ L175J	6,000	✓ L60J	225	✓ L225J
12	✓ L12J12RE	1500	✓ L12J1K5E	12	✓ L12J12RE	1500	✓ L12J1K5E	225	✓ L225J	6,000	✓ L60J	225	✓ L225J	7,500	✓ L75J	500	✓ L500J
15	✓ L12J15RE	2200	✓ L12J2K2E	22	✓ L12J22RE	2700	✓ L12J2K7E	500	✓ L500J	7,500	✓ L75J	500	✓ L500J	10,000	✓ L10K	1000	✓ L1000J
22	✓ L12J22RE	51000	✓ L12J51KE	27	✓ L12J27RE	4700	✓ L12J4K7E	1000	✓ L1000J	10,000	✓ L10K	1000	✓ L1000J	12,000	✓ L12K		
33	✓ L12J33RE			33	✓ L12J33RE	10000	✓ L12J10KE	1000	✓ L1000J	12,000	✓ L12K	1000	✓ L1000J	15,000	✓ L15K		
47	✓ L12J47RE			47	✓ L12J47RE	18000	✓ L12J18KE	1000	✓ L1000J	15,000	✓ L15K	1000	✓ L1000J	20,000	✓ L20K		
68	✓ L12J68RE			68	✓ L12J68RE	22000	✓ L12J22KE	1000	✓ L1000J	20,000	✓ L20K	1000	✓ L1000J	25,000	✓ L25K		
82	✓ L12J82RE			82	✓ L12J82RE			1000	✓ L1000J	25,000	✓ L25K	1000	✓ L1000J	30,000	✓ L30K		
100	✓ L12J100E			100	✓ L12J100E			1000	✓ L1000J	30,000	✓ L30K	1000	✓ L1000J	35,000	✓ L35K		
150	✓ L12J150E			150	✓ L12J150E			1000	✓ L1000J	35,000	✓ L35K	1000	✓ L1000J	40,000	✓ L40K		
								1000	✓ L1000J	40,000	✓ L40K	1000	✓ L1000J	50,000	✓ L50K		
								1000	✓ L1000J	50,000	✓ L50K	1000	✓ L1000J	60,000	✓ L60K		
								1000	✓ L1000J	60,000	✓ L60K	1000	✓ L1000J	75,000	✓ L75K		
								1000	✓ L1000J	75,000	✓ L75K	1000	✓ L1000J	100,000	✓ L100K		
								1000	✓ L1000J	100,000	✓ L100K	1000	✓ L1000J	150,000	✓ L150K		
								1000	✓ L1000J	150,000	✓ L150K	1000	✓ L1000J	200,000	✓ L200K		
								1000	✓ L1000J	200,000	✓ L200K	1000	✓ L1000J	250,000	✓ L250K		
								1000	✓ L1000J	250,000	✓ L250K	1000	✓ L1000J				

✓ = Standard values; check availability using the worldwide inventory search at www.ohmite.com

Red outlined values supplied in Silicone-Ceramic coatings instead of vitreous enamel.