

		REVISIONS			
REV	DESCRIPTION		DATE	APPROVED	
04 ₁	REVISED		K.LE 4-10-97	D.Com 4/10/97	

Technical drawing of a shroud component. The front view shows a cylindrical part with three circular features. Dimensions include a width of .165 (4.2), a height of .282 (7.2), and hole diameters of $\phi .055$ (+.000/-0.001) and $\phi .073$ (+.000/-0.001) (2 PLACES). The side view shows a profile with a total height of $\phi .400$ (10.2), a top flange width of .120 (3.0) with a thickness of $\pm .002$, and a bottom flange width of .045 (1.1) with a thickness of $\pm .002$. A central hole has a diameter of $\phi .165$ (4.2).

SHROUD	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35	
COMPONENT	MATERIAL	FINISH	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°	DRAWN BY E.F.H. CHECKED BY MY APPD BY RAC	DATE 1/13/92 1-15-92 1/15/92	
These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	
	408-04752 NO. AP. (29-006)		TITLE OSMP FULL DETENT SHROUD
	SIZE B		CODE IDENT NO. 26805
SCALE 8:1	REV 04 ₁		
SHEET 1 OF 1			