





LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	APVD
CM	00		F2	REVISED PER ECR-12-010267	05JUN12	JR
			G	REVISED PER ECR-13-011599	08NOV13	AV




- 1 0.00076 [.000030] MIN GOLD IN LOCALIZED GOLD PLATE AREA AND 0.00254 [.000100] MIN BRIGHT TIN-LEAD IN LOCALIZED TIN-LEAD PLATE AREA OVER 0.0013 [.000050] MIN NICKEL.
- 2 WIRE RANGE: 0.12 – 0.4MM² (26-22 AWG).
- 3 INSULATION RANGE: 1.19-1.75[.047-.069] DIA.
- 4 DIMENSIONS IN BRACKETS ARE IN INCHES.
- 5 0.00076 [.000030] MIN GOLD IN LOCALIZED GOLD PLATE AREA AND 0.00254 [.000100] MIN MATTE TIN IN LOCALIZED TIN PLATE AREA OVER 0.0013 [.000050] MIN NICKEL.
- 6 ROHS COMPLIANT.



SECTION A-A
SCALE 20:1



SECTION B-B
SCALE 20:1



SECTION C-C
SCALE 20:1

6	5	0.25[.010] BRASS	1-794219-0
	1	0.25[.010] BRASS	794219-3
	PRE-TIN	0.25[.010] BRASS	794219-1
	FINISH	MATERIAL	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. WHITAKER 04MAR2005	 TE Connectivity						
		CHK C. JONES 04MAR2005							
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD C. JONES 04MAR2005	NAME					
	0 PLC ± -		PRODUCT SPEC	SOCKET, MINI UNIVERSAL MATE-N-LOK(TM) 2 -					
	1 PLC ± -		-						
	2 PLC ± -		-						
	3 PLC ± 0.30 [.012]		APPLICATION SPEC						
	4 PLC ± -		-	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO		
MATERIAL	FINISH		WEIGHT -	A2	00779	C=794219	-		
SEE TABLE	SEE TABLE		CUSTOMER DRAWING				SCALE 10:1	SHEET 1 of 1	REV G