

MICRO SWITCH

FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

ACTUATOR - SWITCH

CATALOG LISTING

JE - 84

JE - 84

M

DRAWING
NUMBER

ISSUE

REPLACES X85274 - JE

RELEASE NO. PR-14836

CHECK

CHECK

2 JUN 66

CHECK


24 JUN 66

CHECK


MAP

FO-52848-A

DRAWN




.012 THICK CORROSION RESISTANT
STEEL LEAF



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS WITH ISEI BASIC SWITCH INSTALLED

OPERATING FORCE --- 12 OZ. MAX

RELEASE FORCE --- 2 OZ. MIN

DIFFERENTIAL TRAVEL --- .025 MAX

OVERTRAVEL --- .015 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT

SCALE FULL

DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR
REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

DIM.	TOL.	DIM.	TOL.
mm	mm/in	in	mm/in
NO PLACES	X	1/.04	
ONE PLACE	X,X	0.4/.018	X,X 0.8/.03
TWO PLACES	X,XX	0.15/.008	X,XX 0.38/.015
THREE PLACES	X,XXX		X,XXX 0.13/.005
ANGLES			

DESIGN UNITS

SI METRIC ☐

US CUSTOMARY ☒

WEIGHT