

Coaxial Cable Connector 16_QN-50-3-3/13-_N

Description

Right angle cable plug

Interface standards

QN QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	11 GHz		
Frequency range	DC to 1 GHz	1 to 6 GHz	6 to 8 GHz
Return loss	24 dB	20 dB	12 dB

Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.019 kg

Environmental Data

Operating temperature	-40 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM (Ethylene propylene diene rubber)	

Related Documents

Outline drawing	DOU-00007941
Catalogue drawing	DOU-00007943
Assembly instruction	DOC-0000183202

Ordering Information

Single package	16_QN-50-3-3/13-_NE
Reuseable package	16_QN-50-3-3/13-_NI

Additional Information

Suitable cables	SUCOFORM_141, EZ_141_TP_M17, MULTIFLEX_141, EZ_141
-----------------	--

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[16_QN-50-3-3/13-_NE](#)