

## Coaxial Panel Connector 23\_4310-50-0-5/003\_-

### Description

Straight panel receptacle jack, flange mount

Interface standards  
IEC 61169-54



### Technical Data

#### Electrical Data

|                          |             |
|--------------------------|-------------|
| Impedance                | 50 $\Omega$ |
| Interface frequency max. | 12 GHz      |

#### Mechanical Data

|                   |           |
|-------------------|-----------|
| Number of matings | 100       |
| Weight            | 0.0394 kg |

#### Environmental Data

|                                                      |                 |
|------------------------------------------------------|-----------------|
| Operating temperature                                | -55 °C to 90 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant       |

#### Material Data

| Piece Parts    | Material                 | Surface Plating       |
|----------------|--------------------------|-----------------------|
| Centre contact | Copper Beryllium / Brass | Silver Plating        |
| Outer contact  | Bronze                   | Silver Plating        |
| Body           | Brass                    | SUCOPLATE (R) Plating |
| Insulator      | PFA / PTFE               |                       |

### Related Documents

|                   |              |
|-------------------|--------------|
| Outline drawing   | DOU-00263954 |
| Catalogue drawing | DCA-00264946 |

### Ordering Information

|                |                       |
|----------------|-----------------------|
| Single package | 23_4310-50-0-5/003_-E |
| Tray package   | 23_4310-50-0-5/003_-Y |

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

23\_4310-50-0-5/003\_-Y