

## Cable gland - VC-M-KV-PG21 4X8 - 1885680

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Multiple screw connection Pg21, made of metal, consisting of rubber seal with several holes (4 x 8 mm) and a pressure screw, for cable screw connection support VC-M-KV-PG21...



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	31.18 g
Custom tariff number	74153300
Country of origin	Poland

### Technical data

#### Dimensions

Wrench size, union nut	30 mm
External cable diameter	7.5 mm ... 8 mm (Cable 1)
	7.5 mm ... 8 mm (Cable 2)
	7.5 mm ... 8 mm (Cable 3)
	7.5 mm ... 8 mm (Cable 4)

#### Ambient conditions

Degree of protection	IP65
	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Type of the screw connection	Half screw connection
No. of conductors	4
Material, pressure screw	Nickel-plated brass
Seal material	TPE

## Cable gland - VC-M-KV-PG21 4X8 - 1885680

### Technical data

#### General

Shielded	No
Thread type on seal side	Pg21
Tightening torque, union nut	10.00 Nm

### Classifications

#### eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27149109

#### ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000441

#### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

### Approvals

#### Approvals

---

Approvals

EAC

---

Ex Approvals

## Cable gland - VC-M-KV-PG21 4X8 - 1885680

### Approvals

Approvals submitted

---

### Approval details

EAC
-----

### Accessories

#### Accessories

Half screw connection - VC-M-KV-PG21- 0 - 1854983

Half screw connection made of metal with rubber seal without hole for sealing or for individual holes

---

### Drawings

Dimensional drawing

