


Passive module - UM- MSTB/8-A-OUT - 2311276

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

VARIOFACE module, for 8 analog outputs, with COMBICON connector, for assembly on NS 35/7.5 or NS 32



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 173766
GTIN	4046356173766

Technical data

Dimensions

Width	64 mm
Height	126 mm
Depth	80 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. perm. operating voltage	30 V DC
Max. perm. current (per branch)	1 A
Mounting position	any
Degree of protection	IP00

Connection data for connection 1

Connection name	COMBICON MSTB
Connection method	Screw/plug-in connection
Conductor cross section solid	0.34 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Connection data for connection 2

Connection name	COMBICON MSTB
Connection method	Screw/plug-in connection
Conductor cross section solid	0.34 mm ² ... 2.5 mm ²

Passive module - UM- MSTB/8-A-OUT - 2311276

Technical data

Connection data for connection 2

Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Standards and Regulations

Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178: 1998-04
Rated insulation voltage	50 V
Rated surge voltage	0.5 kV (1.2/50 μs)
Insulation	Functional insulation
Degree of pollution	2
Overvoltage category	II

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.A*30.B.01742
-----	--	--------------------------