

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	05DEC2016	BS	CW

BEFORE ASSEMBLY:
组装前:

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 2000V
RATED CURRENT: 250A
RATED IMPULSE VOLTAGE: 12KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
WIRE RANGE: 35-70 mm²
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING:T21925010XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 2000V
额定电流: 250A
额定脉冲电压: 12KV
污染等级: 3
阻燃等级: UL94V-0
接线范围: 35-70 mm²
接线类型: 冷压接
- 端子需要单独订购。
(订货号参考图面: T21925010XX000)

AFTER ASSEMBLY:
组装后:

T2192503101-000	HCM250-MC	HCM250 MALE INSERT, CRIMP HCM250公插、冷压型
-----------------	-----------	---

PART NUMBER
零件料号PART DESCRIPTION
零件描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 05DEC2016

BELL SU

CHK 05DEC2016

KYLE ZENG

APVD 05DEC2016

CHRIS WANG

PRODUCT SPEC

108-137171

APPLICATION SPEC

114-137171

WEIGHT

-

CUSTOMER DRAWING

NAME
HCM250-MC

TE Connectivity

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
------	-----------	------------	---------------

A300779 © T2192503101000

-

DIMENSIONS:
mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

MATERIAL

-

FINISH

-

CUSTOMER DRAWING

SCALE 1:1

SHEET 1 OF 1

REV A

1470-19 (3/13)