# XUFAZ01



#### Main

Range of product	OsiSense XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XUC
Sensor design	Compact
Material	Plastic
Electrical connection	Screw-clamp terminals

## Complementary

•			
Lens material	PMMA		
Output type	Solid state		
Wire insulation material	PVC		
Status LED	1 LED (yellow) output state		
[Us] rated supply voltage			
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)	<= 100 mA (overload and short-circuit protection)	
Switching frequency	<= 250 Hz	<= 250 Hz	
Voltage drop	<= 1.5 V (closed state)		
Current consumption	<= 35 mA (no-load)		
Setting-up	Without sensitivity adjustment		

#### **Environment**

ambient air temperature for operation	-13131 °F (-2555 °C)	
ambient air temperature for storage	-40158 °F (-4070 °C)	å
vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6	9
shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27	
IP degree of protection	IP65 double insulation conforming to IEC 60529	

### Offer Sustainability

WARNING: This product can expose you to chemicals	WARNING: This product can expose you to chemicals including:
including:	

Diisononyl phthalate (DINP), which is known to the State Diisononyl phthalate (DINP), which is known to the State of California to cause of California to cause cancer, and

Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

## Contractual warranty

Warranty period	18 months	