

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1719832042](#)
Status: **Active**
Overview: Nano-Pitch I/O™ Interconnect System
Description: Nano-Pitch I/O™ Connector, Vertical Receptacle, Through Hole, with Dust Cap, 42 Circuits

Documents:

3D Model	Packaging Specification PK-173307-0001 (PDF)
Drawing (PDF)	Test Summary TS-171982-0001 (PDF)
Product Specification PS-173162-0001 (PDF)	Test Summary TS-171983-0005 (PDF)
Application Specification AS-173162-0001 (PDF)	RoHS Certificate of Compliance (PDF)
Application Specification AS-173162-0002 (PDF)	

General


Product Family	I/O Connectors
Series	171983
Application	Wire-to-Board
Component Type	Receptacle
Overview	Nano-Pitch I/O™ Interconnect System
Product Name	Nano-Pitch I/O™
Type	N/A
UPC	889056257077

Physical

Circuits (Loaded)	42
Circuits (maximum)	42
Color - Resin	Black
Durability (mating cycles max)	50
Gender	Receptacle
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold over Nickel
Material - Plating Termination	Tin over Nickel
Material - Resin	High Temperature Thermoplastic
Net Weight	0.934/g
Number of Rows	2
Orientation	Vertical
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.57mm
Packaging Type	Embossed Tape on Reel
Panel Mount	No
Pitch - Mating Interface	0.50mm
Pitch - Termination Interface	0.50mm
Plating min - Mating	0.762µm
Plating min - Termination	2.540µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	1
Temperature Range - Operating	-40°C to +80°C
Termination Interface: Style	Through Hole
Waterproof / Dustproof	No

Electrical

Current - Maximum per Contact	0.5A
Grounding to Panel	None



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per
-ED/79/2015 (17
December 2015)

Halogen-Free

Status

Low-Halogen

**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any
non-product compliance questions.

China ROHS
ELV

Green Image
Not Relevant

Search Parts in this Series

[171983](#) Series

Shielded	No
Voltage - Maximum	30V AC (RMS)/DC
Solder Process Data	
Duration at Max. Process Temperature (seconds)	020
Lead-freeProcess Capability	REFLOW
Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	260
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-173162-0001, AS-173162-0002
Electrical Model Document	EE-171983-0005
Packaging Specification	PK-173307-0001
Product Specification	PS-173162-0001
S-Parameter Model	SP-171983-0005
Sales Drawing	SD-171983-1000
Symbol/Footprint Data	SYM-171983-2042
Test Summary	TS-171982-0001, TS-171983-0005

This document was generated on 06/13/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION