

# MALE PCB PINS


## PRINTED CIRCUIT PINS

### 8685/9036

XXXX-0-00-XX-00-00-03-0

Press-fit in .033 mounting hole

Pin material is Phosphor Bronze 544 (B2)




| Basic Part Number | Length A |
|-------------------|----------|
| 8685-0            | .125     |
| 9036-0            | .175     |

### 9051

9051-0-00-XX-00-00-03-0


Press-fit in .057 mounting hole



### 8969

8969-0-05-XX-00-00-03-0


Square press-fit in .023 plated through-hole (Use .7mm drill prior to plating)



### 8979

8979-0-00-XX-00-00-03-0


Hex press-fit in .074 plated through-hole



### 9159

9159-0-00-XX-00-00-03-0


Press-fit in .026 mounting hole



### 3155/5155

X155-0-00-XX-00-00-03-0

Press-fit in .026 mounting hole




| Basic Part Number | Length A |
|-------------------|----------|
| 3155-0            | .180     |
| 5155-0            | .130     |

### 4194

4194-0-00-XX-00-00-08-0


Wire crimp termination & press-fit in .036 hole  
Accepts wire sizes 30 AWG Max. / 36 AWG Min.



### 5556

5556-0-00-XX-00-00-38-0


Wire crimp termination. Accepts wire sizes 30 AWG Max. / 36 AWG Min.



### 3790

3790-0-00-XX-00-00-03-0


Press-fit in .057 mounting hole



### 3796

3796-0-00-XX-00-00-03-0

Press-fit in .057 mounting hole



#### SPECIFICATIONS:

**Pin Material:** Brass Alloy 360, 1/2 Hard  
(Except where noted)

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$   
Diameters:  $\pm .002$   
Angles:  $\pm 2^\circ$



ORDER CODE: XXXX - X - 0X - XX - 00 - 00 - XX - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 200  $\mu$ " TIN/LEAD OVER NICKEL
- 80 200  $\mu$ " TIN OVER NICKEL (RoHS)
- 15 10  $\mu$ " GOLD OVER NICKEL (RoHS)
- 21 20  $\mu$ " GOLD OVER NICKEL (RoHS)
- 34 50  $\mu$ " GOLD OVER NICKEL (RoHS)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com