



## DeviceNet Thin Cables, PVC Grey

0935 614 301 | 0935 614 302 | 0935 614 303



### 0935 614 301/... M

Double-ended cord set, 5 pole 7/8" male straight (external threads) to 5 pole 7/8" female straight connector.

### 0935 614 302/... M

Single-ended cord set, 5 pole 7/8" male straight (external threads) connector.

### 0935 614 303/... M

Single-ended cord set, 5 pole 7/8" female straight connector.

0935 614 310 | 0935 614 306



### 0935 614 310/... M

Double-ended cord set, 5 pole 7/8" male straight (external threads) to 5 pole 7/8" female right angle connector.

### 0935 614 306/... M

Single-ended cord set, 5 pole 7/8" female right-angle connector.

0935 614 309 | 0935 614 307



### 0935 614 309/... M

Double-ended cord set, 5 pole 7/8" male right-angle (external threads) to 5 pole 7/8" female straight connector.

### 0935 614 307/... M

Single-ended cord set, 5 pole 7/8" male right-angle (external threads) connector.



### Pin Assignment

male connector / female connector, 5 poles	Function	Color
Pin 1	Shield	bare
Pin 2	+ 24 V	red
Pin 3	GND (0 V)	black
Pin 4	CAN_H	white
Pin 5	CAN_L	blue



# Be Certain with Belden

## DeviceNet Thin Cables, PVC Grey

### Technical Data

#### Materials

Molded body	PUR, grey
Coupling nut	Aluminum, e-coated or anodized black
Contacts	Brass, gold over nickel plated
Insert	PUR, yellow

#### Electrical

Current rating	4A
Voltage rating	300 V

#### Mechanical

Temperature rating	-20°C to 75°C
Protection	IP 68, NEMA 6P

#### Cable Specifications

General	ODVA Class 2 Thin, Belden cable part number 3084A
Cable jacket	PVC, grey
Overall diameter	.280"
Conductor	2PR 22AWG / 2PR 24AWG
UL approval	CL2, CMG
Drain wire	stranded 22AWG
Shielding	Pairs individually foil shielded overall foil shield and 65% braid

Part Number	Standard Cable Lengths	
0935 614 301/...M	0.3 M   0.6 M   1 M   2 M   3 M   5 M   10 M   15 M	
0935 614 302/...M	0.3 M   0.6 M   1 M   2 M   3 M   5 M   10 M   15 M	
0935 614 303/...M	0.3 M   0.6 M   1 M   2 M   3 M   5 M   10 M   15 M	
0935 614 310/...M	0.3 M   1 M   2 M   3 M   5 M   10 M	
0935 614 306/...M	0.3 M   1 M   2 M   3 M   5 M   10 M	
0935 614 309/...M	0.3 M   1 M   2 M   3 M   5 M   10 M	
0935 614 307/...M	0.3 M   1 M   2 M   3 M   5 M   10 M	