


Relay base - SIM-AMS 1 - 2271015

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plug-in base, for standard I/O modules, with different numbers of contacts, can be labeled with marker pins BN or BNB



Key Commercial Data

Packing unit	10 pc
GTIN	
GTIN	4017918103484

Technical data

Dimensions

Pin dimensions	1,1 x 0,5 mm
Hole diameter	1.4 mm

General

Nominal voltage U_N	250 V AC
	380 V AC
Nominal current I_N	5 A
Number of contacts, type	1
Color	green
Insulating material	PA
Standards/regulations	DIN VDE 0110b, Gr. C for 250 V DC

Standards and Regulations

Connection in acc. with standard	CSA
Standards/regulations	DIN VDE 0110b, Gr. C for 250 V DC

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50

Relay base - SIM-AMS 1 - 2271015


Technical data

Environmental Product Compliance


	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
--	---

Drawings

Dimensional drawing



Schematic diagram



Approvals

Approvals

Approvals

CSA / UL Recognized / EAC

Ex Approvals

Approval details

CSA		http://www.csagroup.org/services-industries/product-listing/	13631
Nominal voltage UN		300 V	
Nominal current IN		5 A	

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 113228
Nominal voltage UN		300 V	

Relay base - SIM-AMS 1 - 2271015

Approvals

Nominal current I _N	5 A

EAC		RU C- DE.A*30.B.01082
-----	---	--------------------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>