REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01_0	RELEASED	1/13/99	S. Morby

.XXX = in
XX.X = mm (REF)



DESIGN CONTROL REQUIRED

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions	Temperature Rating -65°C TO 125°C
Frequency Range (GHz) DC to 18	SCD# 1023376P Fig. 2	Vibration MIL-STD-202, Method
Volt Rating (VRMS MAX)	Recommended Mating	204, Condition B.
@ Sea Level 500	Torque N/A	Shock MIL-STD-202, Method 213,
VSWR 1.09 +.009f(GHz)	Mating Characteristics:	Condition I.
Insertion Loss (dB MAX) .06 @ 1.0-1.2 GHz	Insertion (MAX Lbs) 2.0	Thermal Shock MIL-STD-202,
RF Leakage (dB MIN) -80 @ 1.0 GHz	Withdrawal (MIN Oz) 2.0	Method 107, Condition B
Corona, 70,000 Ft (VRMS MIN) 375	Force to Engage and	Moisture Resistance MIL-STD-202,
Dielectric Withstanding Voltage	Disengage (In-Lbs MAX) 2.0	Method 106. Insulation
(VRMS MIN) @ Sea Level 1,500	Center Contact Captivation	resistance shall be at least
Contact Resistance (Milliohms MAX)	Axial (Lbs) 6.0	200 Meg Ohms within 5 minutes
Center Contact 2.0	Radial (In-Oz) 4.0	of removal from humidity.
Outer Contact 2.0	Weight (Grams) TBD	Corrosion - MIL-STD-202, Method
RF High Potential @ Sea Level		101, Condition B, 5% salt spray
(VRMS MIN @ 5 MHz) 1,000		
I.R.(Megohms MIN) 5,000		

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCE ON
FRAC. ± 1/64 DEC. ±.005 ANGLES ± 1°

DRAWN BY S. Morby DATE 1/13/99
CHECKED BY
APP'D BY S. Morby 1/13/99

AMP

AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

USE ASS'Y PROCEDURE

NO. A.P. N/A

TITLE TNC HIGH-FREQ 2 HOLE FLANGE MOUNT JACK RECEPTACLE TAB TERMINAL

SIZE	CODE IDENT NO.		REV
B	26805	3752-5036-02	01_0

SCALE 5:1 SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1329534-1
SHEET 1 OF 1 REV A