

cannon

# PL Series

Plastic Push Pull Interconnects



ITT

ENGINEERED FOR LIFE

# We Connect

## When it matters most

For more than a century, ITT Cannon has developed innovative interconnect solutions for the world's most critical applications. With facilities in the United States, Germany, Italy, Mexico, China and Japan, each with its unique strengths, we offer our customers interconnect solutions that are truly Engineered for Life.

In addition to this truly global footprint, we offer highly specialized, segmented industry expertise. We have a proven track record as an industry leader in medical and industrial applications. This has equipped us with the knowledge needed to continue to produce the most advanced, resilient and reliable connectors for our customers' most challenging conditions.

## Connecting the world's most important information with those who need it.

Drawing upon nearly 50 years of global presence in the medical industry, ITT Cannon represents a committed partner to medical equipment manufacturers, bringing connector solutions to the applications that help change lives every day.

### The ITT Cannon difference

- Global capabilities & local support
- Proven application expertise
- A century of interconnect leadership
- A committed innovator & business partner

### About ITT

ITT is a diversified leading manufacturer of highly engineered critical components and customized technology solutions for the energy, transportation and industrial markets. Building on its heritage of innovation, ITT partners with its customers to deliver enduring solutions to the key industries that underpin our modern way of life. Founded in 1920, ITT is headquartered in White Plains, N.Y., with employees in more than 35 countries and sales in a total of approximately 125 countries. For more information, visit [www.itt.com](http://www.itt.com).



# ITT Cannon Push Pull PL Series



The ITT Cannon PL Series of plastic push pull interconnects is a high quality, versatile and cost effective solution for challenging medical and industrial applications where miniaturized, lightweight and durable connectors are critical to operating performance.



ITT Cannon's PL Series is a 'Plastic Latching' push pull connector that delivers the ultimate in performance when it matters most. Available in 2 to 14 way variants, with durability in excess of 2,000 mating cycles and with 6 keying options and 7 color codings the PL Series is an extremely versatile solution for a wide variety of both disposable and reusable applications.


Cannon's integrated cable assembly solutions combined with intermateability with existing push pull industry solutions ensures the PL Series is the ultimate choice for today's critical applications.

## Key features

- Innovative self-latching mechanism enables quick and simple mating & un-mating
- Medical grade quality – lightweight and ruggedized
- 6 keying and 7 color coding options enables wide customization
- Available in 2 to 14 way variants
- Accommodates cable sizes  $\varnothing$  2.7 to 6.5 mm
- Fully sterilizable – by gas or steam
- Value added cable assembly solutions available
- Intermateable with existing industry solutions

## Applications

- Medical
  - Electrosurgery tools
  - ECG devices
  - Catheters
  - Sensors
  - Respirators
  - Defibrillators
  - Dental tools
- Industrial electronics
- Test and measurement




# PL Series product overview

## PL Series performance data

|                                    |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| <b>Operating temperature range</b> | PSU: -50 to 150° C (Standard offering)<br>PEI: -50 to 170° C (Contact ITT Cannon) |
| <b>Current rating</b>              | 2 to 10A                                                                          |
| <b>Insulation resistance</b>       | 10 <sup>12</sup> Ω                                                                |
| <b>Voltage</b>                     | 0.6 to 1.2 kV rws                                                                 |

|                                 |                                   |
|---------------------------------|-----------------------------------|
| <b>Ingress protection</b>       | IP50                              |
| <b>Durability</b>               | In excess of 2,000 cycles         |
| <b>Sterilization capability</b> | Can be sterilized by gas or steam |
| <b>Certifications</b>           | UL Certified<br>RoHS compliant    |

## PL Series Push Pull latching system.



## Exploded view of PL Series

|                                     |               |                           |                      |                      |       |
|-------------------------------------|---------------|---------------------------|----------------------|----------------------|-------|
| Straight plug                       |               |                           |                      |                      |       |
|                                     | Backnut       | Cable Collet              | Insulator & Contacts | Shell                |       |
| Straight plug with bend relief      |               |                           |                      |                      |       |
|                                     | Bend Relief   | Bend Relief for a Backnut | Cable Collet         | Insulator & Contacts | Shell |
| Receptacle with back panel mounting |               |                           |                      |                      |       |
|                                     | Hexagonal Nut | Shell                     | Front Nut            |                      |       |
| In-line receptacle                  |               |                           |                      |                      |       |
|                                     | Backnut       | Cable Collet              | Insulator & Contacts | Shell                |       |
| In-line receptacle with bend relief |               |                           |                      |                      |       |
|                                     | Bend Relief   | Bend Relief for a Backnut | Cable Collet         | Insulator & Contacts | Shell |

# PL Series part number system



## Straight plug and inline receptacle

| PL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | XX | X | X | X | X | X | XX |                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---|---|---|---|---|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Push pull plastic</p> <p>Straight plug<br/>In-line receptacle</p> <p>A1= straight plug with cable collet ---- solder contact<br/>A3= straight plug with cable collet and nut for fitting a bend relief ---- solder contact<br/>C1= In-line receptacle with cable collet ---- solder contact<br/>C3= In-line receptacle with cable collet and nut for fitting a bend relief ---- solder contact</p> <p>Outer shell material:<br/>G= Grey PSU(standard) F= Black PEI<br/>B= Black PSU P=Grey PEI</p> <p>Back nut color:<br/>0= Black 1= White 2= Red 4= Yellow 5= Green 6= Blue 8= Grey</p> |    |   |   |   |   |   |    | <p>Number of contacts:<br/>02= 2Pin 03= 3Pin 04= 4Pin<br/>05= 5Pin 06= 6Pin 07= 7Pin<br/>08= 8Pin 09= 9Pin 10= 10Pin<br/>14= 14Pin</p> <p>Coding:<br/>0= 0° (standard)<br/>A= 40° C=60°<br/>E= 80° H= 170° J=205°</p> <p>Cable collet:<br/>1=ø3.9mm (cable ø=2.7~3.9mm)<br/>2=ø5.2mm (cable ø=4.0~5.2mm)<br/>3=ø6.5mm (cable ø=5.3~6.5mm)</p> <p>Contact plating:<br/>2= Gold plating 20u''</p> |

For A3 and C3 the Back nut is only available in Grey (8)

For A3 and C3 type, please order bend relief separately.

## Receptacle

| PL                                                                                                                                                                                                                                                                                                                                                                                                                                                              | XX | X | X | X | X | X | XX |                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---|---|---|---|---|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Push pull plastic</p> <p>Receptacle<br/>B1= Receptacle with two nuts (back panel mounting) ----solder contact<br/>B3= Receptacle with two nuts, (back panel mounting) ----with 90 degree PCB contact<br/>B4= Receptacle, front nut fixing ----solder contact</p> <p>Outer shell material:<br/>G= Grey PSU(standard) F= Black PEI<br/>B= Black PSU P=Grey PEI</p> <p>Front nut color:<br/>0= Black 1= White 2= Red 4= Yellow<br/>5= Green 6= Blue 8= Grey</p> |    |   |   |   |   |   |    | <p>Number of contacts:<br/>02= 2Pin 03= 3Pin 04= 4Pin<br/>05= 5Pin 06= 6Pin 07= 7Pin<br/>08= 8Pin 09= 9Pin 10= 10Pin<br/>14= 14Pin</p> <p>Coding:<br/>0= 0° (standard)<br/>A= 40° C=60°<br/>E= 80° H= 170° J=205</p> <p>Cable collet:<br/>0= no cable collet</p> <p>Contact plating:<br/>2= Gold plating 20u''</p> |


## Bend relief

| PL                                                                                                                        | BR           | X   | XXX0 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
|---------------------------------------------------------------------------------------------------------------------------|--------------|-----|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--------------|--|-----|-----|-----|------|---|-----|------|-----|-----|------|---|-----|------|-----|-----|------|---|-----|------|-----|-----|------|---|-----|------|-----|
| <p>Push pull plastic</p> <p>Bend relief</p> <p>Color:<br/>0= Black 2= Red 3= White 4= Yellow 5= Green 6= Blue 8= Grey</p> |              |     |      | <table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">Cable n (mm)</th> </tr> <tr> <th>Min</th> <th>Max</th> </tr> </thead> <tbody> <tr> <td>025</td> <td>&gt;2.5</td> <td>3</td> </tr> <tr> <td>030</td> <td>&gt;3.0</td> <td>3.5</td> </tr> <tr> <td>035</td> <td>&gt;3.5</td> <td>4</td> </tr> <tr> <td>040</td> <td>&gt;4.0</td> <td>4.5</td> </tr> <tr> <td>045</td> <td>&gt;4.5</td> <td>5</td> </tr> <tr> <td>050</td> <td>&gt;5.0</td> <td>5.5</td> </tr> <tr> <td>055</td> <td>&gt;5.5</td> <td>6</td> </tr> <tr> <td>060</td> <td>&gt;6.0</td> <td>6.5</td> </tr> </tbody> </table> |  | Cable n (mm) |  | Min | Max | 025 | >2.5 | 3 | 030 | >3.0 | 3.5 | 035 | >3.5 | 4 | 040 | >4.0 | 4.5 | 045 | >4.5 | 5 | 050 | >5.0 | 5.5 | 055 | >5.5 | 6 | 060 | >6.0 | 6.5 |
|                                                                                                                           | Cable n (mm) |     |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
|                                                                                                                           | Min          | Max |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
| 025                                                                                                                       | >2.5         | 3   |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
| 030                                                                                                                       | >3.0         | 3.5 |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
| 035                                                                                                                       | >3.5         | 4   |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
| 040                                                                                                                       | >4.0         | 4.5 |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
| 045                                                                                                                       | >4.5         | 5   |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
| 050                                                                                                                       | >5.0         | 5.5 |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
| 055                                                                                                                       | >5.5         | 6   |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |
| 060                                                                                                                       | >6.0         | 6.5 |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |              |  |     |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |     |      |   |     |      |     |


Dimensions shown in mm

# PL Series straight plug and receptacles



## Straight Plug



## Receptacle




## A1 Straight plug with cable collet



## A3 Straight plug with cable collet and nut for bend relief



## B1 Receptacle with two nuts




| Number of Contacts | Dimensions |     |
|--------------------|------------|-----|
|                    | A          | B   |
| 02                 | 2.5        | -   |
| 03                 |            | -   |
| 04                 |            | -   |
| 05                 |            | -   |
| 06                 |            | -   |
| 07                 |            | 3.9 |
| 08                 |            | 3.9 |
| 09                 |            | 3.9 |
| 10                 |            | 3.9 |
| 14                 |            | 3.9 |

Solder to board and crimp contacts are available. Contact ITT Cannon for details.


Dimensions shown in mm

# PL Series receptacles

## B3 Receptacle with 90° contacts



| Number of Contacts | Dimensions |     |
|--------------------|------------|-----|
|                    | A          | B   |
| 02                 | 2.5        | -   |
| 03                 |            | -   |
| 04                 |            | -   |
| 05                 |            | -   |
| 06                 |            | -   |
| 07                 |            | 3.9 |
| 08                 |            | 3.9 |
| 09                 |            | 3.9 |
| 10                 |            | 3.9 |
| 14                 |            | 3.9 |





## B4 Receptacle with nut fixing



Solder to board and crimp contacts are available. Contact ITT Cannon for details.

## C1 In-line receptacle with with cable collet



## C3 In-line receptacle for bend relief




Dimensions shown in mm

[www.ittcannon.com](http://www.ittcannon.com)

# PL Series bend relief and housing models

## Bend Relief






| Part Number | Cable Ø (mm) |      |
|-------------|--------------|------|
|             | Min.         | Max. |
| 025         | >2.5         | 3.0  |
| 030         | >3.0         | 3.5  |
| 035         | >3.5         | 4.0  |
| 040         | >4.0         | 4.5  |
| 045         | >4.5         | 5.0  |
| 050         | >5.0         | 5.5  |
| 055         | >5.5         | 6.0  |
| 060         | >6.0         | 6.5  |

| Colour Code | 0     | 2   | 3     | 4      | 5     | 6    | 8    |
|-------------|-------|-----|-------|--------|-------|------|------|
| Colour      | Black | Red | White | Yellow | Green | Blue | Grey |

## Housing Models

STRAIGHT PLUGS









A1

A3

FLUIDIC PLUG

RECEPTACLE



B1



B4

BE

BF

FLUIDIC RECEPTACLE

IN-LINE RECEPTACLE



C1

C3

For fluidic, BE and BF options please contact ITT Cannon.

# PL Series product options



## Insert Configurations

| Number of contacts                   |        | 02  | 03  | 04   | 05   | 06   | 07   | 08   | 09   | 10   | 14   |
|--------------------------------------|--------|-----|-----|------|------|------|------|------|------|------|------|
| View from termination side           | Male   |     |     |      |      |      |      |      |      |      |      |
|                                      | Female |     |     |      |      |      |      |      |      |      |      |
| Test voltage (kv rms)                |        | 1.2 | 1.2 | 1.2  | 1.05 | 1.05 | 1.05 | 1.05 | 0.85 | 0.85 | 0.6  |
| Rated current                        |        | 10  | 10  | 8    | 7    | 6    | 5    | 5    | 3    | 3    | 2    |
| Creepage and clearance (mm) distance |        | 1.3 | 1.3 | 1.2  | 0.8  | 0.85 | 0.85 | 0.6  | 0.65 | 0.5  | 0.5  |
| Max, AWG                             |        | 20  | 20  | 22   | 22   | 26   | 26   | 26   | 28   | 28   | 28   |
| Solder bucket Ø(mm)                  |        | 1.1 | 1.1 | 0.85 | 0.85 | 0.65 | 0.65 | 0.65 | 0.45 | 0.45 | 0.45 |
| Contact Ø(mm)                        |        | 1.3 | 1.3 | 0.9  | 0.9  | 0.7  | 0.7  | 0.7  | 0.5  | 0.5  | 0.5  |

## Alignment Key

| Part Number     |   |   |   |   |   |   |
|-----------------|---|---|---|---|---|---|
| CODING          | 0 | A | C | E | H | J |
| PLUG FRONT VIEW |   |   |   |   |   |   |

## Color Coding

| Part Number               |         |       |          |         |        |        |
|---------------------------|---------|-------|----------|---------|--------|--------|
| Front and back nut colors |         |       |          |         |        |        |
| 0=Black                   | 1=White | 2=Red | 4=Yellow | 5=Green | 6=Blue | 8=Grey |

## Outer Shell Material

| Part Number |               |               |
|-------------|---------------|---------------|
| Material    | PSU           | PEI           |
| Temperature | -50° / +150°C | -50° / +170°C |
| Part number | G=Grey PSU    | F=Black PEI   |
|             | B=Black PSU   | P=Grey PEI    |

## Contact Diameter

| Part Number                      |  |
|----------------------------------|--|
| 1=Ø1.3mm (only for 2; 3 pin)     |  |
| 2=Ø0.9mm (only for 4; 5 pin)     |  |
| 3=Ø0.7mm (only for 6; 7; 8 pin)  |  |
| 4=Ø0.5mm (only for 9; 10; 14pin) |  |

## Gold Plating

| Part Number        |  |
|--------------------|--|
| 2=Gold plated 20u" |  |












## Cable Collet

| Part Number                     |  |
|---------------------------------|--|
| 1=Ø3.9mm (Cable Ø=2.7~3.9mm)    |  |
| 2=Ø5.2mm (Cable Ø=4.0~5.2mm)    |  |
| 3=Ø6.5mm (Cable Ø=5.3~6.5mm)    |  |
| 0=No cable collet (B type only) |  |











Dimensions shown in mm

# PL Series PCB drilling detail


For 90° Elbow contacts, see from A-A view.

|                                                                                                |                                                                                                  |                                                                                                   |                                                                                                  |
|------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
|               | <p>2 PIN</p>    | <p>3 PIN</p>    | <p>4 PIN</p>  |
| <p>5 PIN</p>   | <p>6 PIN</p>    | <p>7 PIN</p>    | <p>8 PIN</p>  |
| <p>9 PIN</p>  | <p>10 PIN</p>  | <p>14 PIN</p>  |                                                                                                  |

For straight contacts

|                                                                                                  |                                                                                                  |                                                                                                  |                                                                                                    |                                                                                                     |
|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
|  <p>2 PIN</p> |  <p>3 PIN</p> |  <p>4 PIN</p> |  <p>5 PIN</p>  |  <p>6 PIN</p>  |
|  <p>7 PIN</p> |  <p>8 PIN</p> |  <p>9 PIN</p> |  <p>10 PIN</p> |  <p>14 PIN</p> |

Panel Cutout



Dimensions shown in mm

# Additional advanced, resilient and reliable solutions from ITT Cannon



## DL

The DL Series of Zero Insertion Force (ZIF) connectors are high performance, multiple-wire power and signal connectors with a minimum rated life of 10,000 mating cycles.



## QLC

The miniaturized QLC series is a durable, highly reliable and easily assembled high pin count connector solution for today's portable medical and industrial applications.



## DLP

The DLP series of connectors provide extremely reliable performance with minimized signal paths and crosstalk as the innovative design ensures receptacle contacts mate directly to the PCB.



## Universal Contact

The UC series has a singular contact design which exhibits over 0.3N of force with only 0.1mm of deflection and provides the ultimate dry circuit pressure contact for commercial and handheld applications.



## APD

APD is a full-plastic, proven bayonet series with IP69K sealing and color and mechanical coding that is an ideal solution for critical environments that require high sealing grades.



## Customized Cable Assemblies

ITT Cannon has value added cable assembly capabilities at its global engineering centers and the proven expertise to partner with customers to develop specialized assemblies for any application.

Connect with your ITT Cannon representative  
today or visit us at [www.ittcannon.com](http://www.ittcannon.com)

## Connect with the experts

ITT Cannon is a world leader in the design and manufacture  
of highly engineered solutions for multiple end markets.



ENGINEERED FOR LIFE

---

### North America

56 Technology Drive  
Irvine, CA 92618  
Phone +1.800.854.3028

100 New Wood Road  
Watertown, CT 06795  
Phone: +1.860.274.9681

### Europe

Italy  
Corso Europa 41/43  
I - 20020 Lainate (MI) Italy  
Phone: +39.02938721

Germany  
Cannonstrasse 1  
71384 Weinstadt, Germany  
Phone: +49.7151.699.0

### Asia

Hong Kong  
Units 2405-6, 24/F, ING Tower  
308 Des Voeux Road Central, Hong Kong  
Phone: +852.2732.2720