

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:0430450229

Status:Active

Overview:Micro-Fit 3.0™ Connectors

Description:Micro-Fit 3.0™ Vertical Header, 3.00mm Pitch, Dual Row, 2 Circuits, with PCB Polarizing Peg, Gold, Glow Wire Compliant, Black

Documents:

- 3D Model
- Drawing (PDF)
- Product Specification PS-43045 (PDF)
- Test Summary TS-43045-001 (PDF)
- Test Summary TS-43045-002 (PDF)
- RoHS Certificate of Compliance (PDF)
- Product Literature (PDF)

Agency Certification

CSA

UL

LR19980

E29179

General

Product Family

Series

Application

Comments

PCB Headers

43045

Power, Wire-to-Board

"This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options."

Overview

Product Literature Order No

Product Name

UPC

Micro-Fit 3.0™ Connectors

987650-5984

Micro-Fit 3.0™

800753808768

Physical

Breakaway

Circuits (Loaded)

Circuits (maximum)

Color - Resin

Durability (mating cycles max)

Flammability

Glow-Wire Compliant

Lock to Mating Part

Mated Height

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

No

2

2

Black

30

94V-0

Yes

Yes


17.27mm

Brass

Gold

Tin

High Temperature Thermoplastic



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Contains SVHC(17. December 2014): No

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

Green Image

Not Relevant

Search Parts in this Series

43045 Series

Mates With

43025 Micro-Fit 3.0™ Receptacle Housing

|                                                |                                        |
|------------------------------------------------|----------------------------------------|
| Net Weight                                     | 0.480/g                                |
| Number of Rows                                 | 2                                      |
| Orientation                                    | Vertical                               |
| PC Tail Length                                 | 3.18mm                                 |
| PCB Locator                                    | Yes                                    |
| PCB Retention                                  | None                                   |
| PCB Thickness - Recommended                    | 1.60mm                                 |
| Packaging Type                                 | Tray                                   |
| Pitch - Mating Interface                       | 3.00mm                                 |
| Plating min - Mating                           | 0.762μm                                |
| Polarized to PCB                               | Yes                                    |
| Shrouded                                       | Fully                                  |
| Stackable                                      | No                                     |
| Surface Mount Compatible (SMC)                 | Yes                                    |
| Temperature Range - Operating                  | -40°C to +105°C                        |
| Termination Interface: Style                   | Through Hole                           |
| <b>Electrical</b>                              |                                        |
| Current - Maximum per Contact                  | 5.0A                                   |
| Voltage - Maximum                              | 600V                                   |
| <b>Solder Process Data</b>                     |                                        |
| Duration at Max. Process Temperature (seconds) | 030                                    |
| Lead-freeProcess Capability                    | SMC&WAVE                               |
| Max. Cycles at Max. Process Temperature        | 003                                    |
| Process Temperature max. C                     | 260                                    |
| <b>Material Info</b>                           |                                        |
| <b>Reference - Drawing Numbers</b>             |                                        |
| Product Specification                          | PS-43045, RPS-43045-003, RPS-43045-004 |
| Sales Drawing                                  | SD-43045-010                           |
| Test Summary                                   | TS-43045-001, TS-43045-002             |

This document was generated on 07/10/2015

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**