
SPECIFICATIONS			
PARAMETERS	VALUES	UNITS	
RATED VOLTAGE	24	Vdc	
OPERATING VOLTAGE RANGE	15 ~ 27	Vdc	
RATED CURRENT (MAX)	30	mA	
MINIMUM SPL @ 10 CM	81	dBA	
RESONANT FREQUENCY	400 ± 100	Hz	
TONE OR PULSE RATE	CONTINUOUS	0 pulse /sec	
OPERATING TEMPERATURE	-10 ~ +60	ů	
STORAGE TEMPERATURE	-20 ~ +70	°C	
HOUSING MATERIAL	ABS	-	
TERMINAL MATERIAL	Sn PLATED COPPER	-	
WEIGHT	10	grams	


THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS.


UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

Υ		REVISION HISTORY		
R	LTR	DESCRIPTION	DATE	APPROVED
	-	RELEASED FROM ENGINEERING	5/24/2006	
	Α	A ADDED BODY DIMENSION		R.W.
	В	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	12/19/2007	B.R.









NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN MILLIMETERS.	SIZE
TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.	A3
AI-2304-TT-24V-R.idw	

J.D.	5/24/2006	Е
	pui,	
	a projects unlimited co	Inc

Date

Designed by

Checked by	Date	Approved by	Date	Drawn Date	
E.P.	5/25/2006	B.R.	5/25/2006	12/19/2007	
AI-2304-TT-24V-R					

Indicator Edition Sheet 1 / 1

4