T3/DS3/E3/STS-1 TRANSFORMERS

Dual SMT, Extended Temperature Range







- RoHS peak reflow temperature rating: 245°C
- Dual SMT package contains both transmit and receive transformers
- Operating temperature of -40°C to +85°C
- Models matched to leading transceiver ICs
- Return loss meets requirements of G.703
- 1500 Vrms isolation per UL1459 and UL195 0


Electrical Specifications @ 25°C — Operating Temperature - 40°C to +85°C												
RoHS-6 Compliant Part Number	Turns Ratio (±2%)		OCL Primary @ 25°C (µH MIN)		L _L (μΗ ΜΑΧ)		C ww (pF MAX)		Isolation Voltage	Package/ Schematic	Primary Pins	
	TX	RX	TX	RX	TX	RX	TX	RX	(Vrms MIN)		TX	RX
T3020NL	1:2CT	1:1	40	100	.120	.120	10	10	1500	BH/1	16-14	6-8
T3023NL	1:1	1:1	40	40	.110	.110	10	10	1500	BH/2	1-2	7-8

Mechanical Schematics

BH







 Weight
 1.0 grams

 Tape & Reel
 600/reel

 Tube
 40/tube

Dimensions: Inches

Unless otherwise specified, all tolerances are $\pm \frac{.010}{0.25}$

USA 858 674 8100 • Germany 49 7032 7806 0 • Singapore 65 6287 8998 • Shanghai 86 21 32181071 • China 86 755 33966678 • Taiwan 886 3 4643715

T3/DS3/E3/STS-1 TRANSFORMERS

Dual SMT, Extended Temperature Range



Application Notes

- 1. The transformers have been developed for use as transmit and receive transformers in T3 or DS3 links, using bit rates of 44.736Mbps and B3ZS coding on coaxial cable. The characteristics allow compliance with the pulse templates of CCITT G.703 as well as ATT T.A.34. The transformers are also suitable for the E3 interface at 34.368Mbps with HDB3 coding or STS-1applications, at 51.84Mbps according to Bellcore TA-NWT-000253.
- **2.** Bandwidth specifications are typical in a 75 Ω system. Return loss meets the requirements of G.703. Materials used in the products are UL94-V0 recognized. Products meet the requirements of IEC 695-2-2 (Needle Flame Test).

- 3. For those applications requiring a 1:1 turns ratio on the transmit side, use only one half of the secondary (2CT) winding.
- **4.** Optional Tape & Reel packaging can be ordered by adding a "**T**" suffix to the part number (i.e. T3023NLT).
- 5. For other T3/DS3/E3/STS-1 Transformers, please see data sheets T606, T619, T672, T663 and T668.
- **6.** Transformer Selection Guide Please contact Pulse Applications Engineering or see the Pulse web site Data Sheet Menu to find the latest Transformer Selection Guide.

For More Information:

Pulse Worldwide Headquarters

12220 World Trade Dr. D-71083 Herrenberg San Diego, CA 92128

www.pulseeng.com

Fax: 858 674 8262

Tel: 49 7032 7806 0 Tel: 858 674 8100 Fax: 49 7032 7806 135

Pulse Europe

Finsteinstrasse 1

Germany

Pulse China Headquarters

B402, Shenzhen Academy of Aerospace Technology Bldg. 10th Kejinan Rd. High-Tech Zone Nanshan District Shenzen, PR China 518057 TEL: 86 755 33966678 FAX: 86 755 33966700

Pulse North China

Room 1503 XinYin Building No. 888 YiShan Rd. Shanghai 200233 China

Tel: 86 21 54643211/2 Fax: 86 21 54643210

Pulse South Asia 135 Joo Seng Rd.

#03-02 PM Industrial Bldg. Singapore 368363

TEL: 65 6287 8998 FAX: 65 6280 0080 **Pulse North Asia**

No. 26, Kao Ching Rd. Yang Mei Chen Taoyuan Hsien Taiwan R. O. C.

Tel: 886 3 4643715 Fax: 886 3 4641911

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2009. Pulse Engineering, Inc. All rights reserved.