





LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN
ES	00		J1	REV PER ECR-12-016975	25SEP2012	CZ
			J3	ADDED NEW DASH NUMBER 4-0	01FEB2013	SZ
			J5	ADDED NEW DASH NUMBER 4-1	25FEB2014	SZ



- 1 OPTIONAL CENTER MODULE, WITH .150 THRU HOLE OR HOLD DOWN FEATURE.
- 2 "AMP", PART NUMBER AND DATE CODE TO BE MARKED
- 3 MATERIAL: HOUSING - GLASS FILLED HIGH TEMP THERMO PLASTIC, UL94 V-0.
SIGNAL CONTACT - HIGH CONDUCTIVITY COPPER ALLOY
POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY
- 4 CONTACT PLATING: NOBLE METAL PLATING ON CONTACT FUNCTIONAL AREA OF POWER AND SIGNAL CONTACTS
- 5 MECHANICAL CONNECTOR KEEP OUT ZONE.
- 6 DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 7 PCB - ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES
- 8 PCB - .0453±.0010 DRILLED HOLES PLATED WITH .0003 MIN Sn OVER .001 TO .003 Cu PLATING TO ACHIEVE A .040 DIAMETER HOLE



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R.GRZYBOWSKI 21FEB05	TE Connectivity	
		CHK M.PERCHEKKE 21FEB05		
DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD M.PERCHEKKE	NAME	
INCHES	0 PLC ±"	PRODUCT SPEC	RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL	
	1 PLC ±.01	108-1973		
	2 PLC ±.01	APPLICATION SPEC	SIZE CAGE CODE DRAWING NO	
	3 PLC ±.005	114-13038	A100779C=6450170	
	4 PLC ±.0020	WEIGHT	RESTRICTED TO	
	ANGLES ±2°			
MATERIAL	FINISH	CUSTOMER DRAWING	SCALE 4:1 SHEET 1 OF 13 REV J5	


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
ES	00	-	-	SEE SHEET 1	-	-	-

J4

2.650	.200	.250	1.550	.875	2.700	-	3.000	.450	2P + 24S + 6P	4-6450170-1
3.100	.250	.250	2.250	1.875	3.150	-	3.450	.450	6P + 12S + 4P	4-6450170-0
1.900	.250	.300	1.550	1.275	1.950	-	2.250	.475	3ACP + 8S + 2P	3-6450170-9
1.800	-	-	1.700	.625	1.850	-	2.150	.450	1P + 40S + 1P	3-6450170-8
1.600	-	-	1.500	.625	1.650	-	1.950	.450	1P + 32S + 1P	3-6450170-7
1.700	.250	.250	1.350	.875	1.750	-	2.050	.450	2P + 16S + 2P	3-6450170-6
1.550	.250	.250	1.200	.900	1.600	-	1.900	.450	2P + 8S + 2P	3-6450170-5
2.350	.250	.250	1.250	.875	2.400	-	2.700	.450	2P + 12S + 5P	3-6450170-4
2.325	.250	.300	1.975	1.600	2.375	-	2.675	.450	4ACP + 12S + 2P	3-6450170-3
1.700	.250	.250	1.350	.875	1.750	-	2.050	.450	2P + 16S + 2P	3-6450170-1
2.300	.250	.300	1.950	1.275	2.350	-	2.650	.450	3ACP + 24S + 2P	3-6450170-0
2.400	.250	.250	1.800	1.125	2.450	-	2.750	.450	3P + 24S + 3P	2-6450170-9
2.300	.250	.300	1.950	1.275	2.350	-	2.650	.450	3ACP + 24S + 2P	2-6450170-8
2.400	.250	.250	1.800	1.125	2.450	-	2.750	.450	3P + 24S + 3P	2-6450170-7
1.950	.250	.250	1.600	1.125	2.000	-	2.300	.450	3P + 16S + 2P	2-6450170-6
1.300	-	-	1.200	.675	1.350	-	1.650	.450	1P + 16S + 1P	2-6450170-0
2.200	.250	.250	1.350	.875	2.250	-	2.550	.450	2P + 16S + 4P	1-6450170-9
2.800	.300	.250	2.075	1.375	2.850	-	3.150	.450	4P + 24S + 3ACP	1-6450170-8
3.000	.250	.250	2.150	1.425	3.050	-	3.350	.450	4P + 24S + 4P	1-6450170-4
2.600	.200	.200	1.925	1.175	2.650	-	2.950	.425	4P + 28S + 4P	1-6450170-1
1.575	-	-	1.425	.700	1.625	-	1.925	.475	1P + 24S + 1P	1-6450170-0
2.500	.250	.250	2.150	.875	2.550	-	2.850	.450	2P + 48S + 2P	6450170-9
3.300	.250	.300	1.950	1.275	3.350	-	3.650	.475	3ACP +24S + 6P	6450170-8
1.400	.250	.250	1.300	.625	1.450	-	1.750	.450	1P + 24S + 1P	6450170-6
2.400	.250	.250	1.800	1.125	2.450	-	2.750	.450	3P + 24S + 3P	6450170-5
4.350	.250	.250	3.500	2.625	4.400	-	4.700	.450	9P + 32S + 4P	6450170-4
3.650	.250	.300	2.550	1.275	3.700	-	4.000	.475	3ACP + 48S + 5P	6450170-3
3.050	.250	.300	1.950	1.275	3.100	-	3.400	.475	3ACP +24S + 5P	6450170-2
2.550	.250	.300	2.200	1.525	2.600	-	2.900	.475	3ACP+1P+24S+2P	6450170-1
DIM U	DIM T	DIM S	DIM R	DIM W	DIM D	DIM M	DIM L	DIM K	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES



MATERIAL
-

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC
1 PLC
2 PLC
3 PLC
4 PLC
ANGLES
FINISH

±
±.01
±.005
±.0020
#2°
-

DWN
R.GRZYBOWSKI

CHK
M.PERCHEKKE

APVD
M.PERCHEKKE

PRODUCT SPEC
108-1973

APPLICATION SPEC
114-13038

WEIGHT
-

CUSTOMER DRAWING

21FEB05

21FEB05

-

NAME
RIGHT ANGLE RECEPTACLE ASSEMBLY
WITH GUIDES
MULTI-BEAM XL

SIZE
A1

CAGE CODE
100779

DRAWING NO
6450170

RESTRICTED TO
-



SCALE
4:1

SHEET
2

OF
13

REV
J5


4805 (3/11)




THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG: R. GRZYBOWSKI 21FEB05 CHK: M. PERCHERKE 21FEB05		 TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±. 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0020 ANGLES 42°		NAME: RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL	
		APVD: M. PERCHERKE PRODUCT SPEC 108-1973 APPLICATION SPEC 114-13038		SIZE: CAGE CODE: DRAWING NO: A100779C6450170	
MATERIAL: - FINISH: -		WEIGHT: -		RESTRICTED TO: -	
CUSTOMER DRAWING				SCALE: 1:1 SHEET 3 OF 13 REV. 1	

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
ES	00	-	-	SEE SHEET 1	-	-	-


PART NUMBER	ROWS		POWER			SIGNAL						POWER				
			P6	P5	P4	6	5	4	3	2	1	P3	P2	P1		
6450170-5	D C B A		RA	RM	RM	H	G	H	G	H	H	H	RM	RM	RA	
						G	G	G	G	G	G	G				
						F	F	F	F	F	F	F				
						E	E	E	E	E	E	E				
3P + 24S + 3P			HD													




PART NUMBER	ROWS	POWER		SIGNAL							POWER	
		P2		6	5	4	3	2	1	P1		
6450170-6	D C B A	RB	K	K	K	K	K	K	K	RN	HD	
1P + 24S + 1P		HD										




PART NUMBER	ROWS		POWER						SIGNAL						POWER			
			P9	P8	P7	P6	P5	P4	6	5	4	3	2	1	P3	P2	P1	
6450170-8	D C B A		RM	RM	RM	RM	RM	RM	H	H	H	H	H	H	RA	RM	RM	
3ACP + 24S + 6P			HD															



PART NUMBER	ROWS			POWER		SIGNAL												POWER																																																																																																																																																																																																																																																																																																																																																																									
		P4	P3	12	11	10	9	8	7	6	5	4	3	2	1	P2	P1																																																																																																																																																																																																																																																																																																																																																																										
6450170-9	D C B A																																																																																																																																																																																																																																																																																																																																																																																										<




THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. GRZYBOWSKI	21FEB05	TE Connectivity	
DIMENSIONS: INCHES		CHK M. PERCHERKE	21FEB05		
		APVD M. PERCHERKE	-	NAME	
		PRODUCT SPEC	-	RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL	
MATERIAL -		APPLICATION SPEC	108-1973	SIZE	
		ANGLES ±.0020	114-13038	CAGE CODE	
FINISH -		WEIGHT -	-	DRAWING NO	
		CUSTOMER DRAWING	-	A100779	
		SCALE		SHEET	
		4:1		4 OF 13	
				REV	
				J5	

[illegible]

PART NUMBER	ROWS		POWER			SIGNAL							POWER																			
			P6	P5	P4	6	5	4	3	2	1	P3	P2	P1																		
2-6450170-7	D C B A																															
3P + 24S + 3P																																

PART NUMBER	ROWS		POWER			SIGNAL							POWER			
			P6	P5	P4	6	5	4	3	2	1	P3	P2	P1		
2-6450170-9	D C B A	HD	RM	RM	RA	H G F E	H G F E	H G F E					RM		RM	HD
3P + 24S + 3P																




—NO CONTACTS LOADED



4805 (3/11)

LOC		DIST		REVISONS			
P	LYR	DESCRIPTION		DATE	DWN	APVD	
-	-	SEE SHEET 1		-	-	-	

PART NUMBER	ROWS		POWER				SIGNAL				POWER		
			P6	P5	P4	P3	4	3	2	1	P2	P1	
1-6450170-9	D		RA	RA	RM	RM	H	H	H	H	RM	RA	
	C						G	G	G	G			
	B						F	F	F	F			
	A						E	E	E	E			
2P + 16S + 4P													



PART NUMBER	ROWS		POWER				SIGNAL						POWER				
			P8	P7	P6	P5	6	5	4	3	2	1	P4	P3	P2	P1	
1-6450170-4	D C B A	 HD	 RA	 RA	 RA	 RA	H	H	H	H	H	H	 RA	 RA	 RA	 RA	 HD
							G	G	G	G	G	G					
							F	F	F	F	F	F					
							E	E	E	E	E	E					
4P + 24S + 4P																	




PART NUMBER	ROWS		POWER		SIGNAL						AC POWER			
			P5	P4	6	5	4	3	2	1	P3	P2	P1	
2-6450170-8	D		RA	RA	H	H	H	H	H	H	RA	RM	RM	
	G				G	G	G	G	G					
	F				F	F	F	F	F					
	E				E	E	E	E	E					
3ACP + 24S + 2P														


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. GRZYBOWSKI 21FEB05	TE Connectivity	
DIMENSIONS: INCHES		CHK M. PERCHERKE	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD M. PERCHERKE	RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL	
0 PLC ±.01		PRODUCT SPEC	SIZE	
1 PLC ±.01		108-1973	CAGE CODE	
2 PLC ±.005		APPLICATION SPEC	DRAWING NO	
3 PLC ±.002		114-13038	REV	
4 PLC ±.002		WEIGHT	A100779	
ANGLES FINISH		CUSTOMER DRAWING	SCALE 4:1	
MATERIAL		SHEET 6 OF 13		REV J5

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER	SIGNAL				POWER		
			P2	4	3	2	1	P1		
2-6450170-0	D C B A		RM	H	H	H	H	RM		
				G	G	G	G			
				F	F	F	F			
		HD		E	E	E	E		HD	
IP + 16S + IP										



PART NUMBER	ROWS		POWER		SIGNAL							AC POWER			
			P5	P4	6	5	4	3	2	1	P3	P2	P1		
3-6450170-0	D C B A		RM	RM	H	H	H	H	H	H	RA	RM	RM		
					G	G	G	G	G	G					
					F	F	F	F	F	F					
				HD			E	E	E	E	E	E			
3ACP + 24S + 2P															



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
R.GRZYBOWSKI
CHK
M.PERCHEKKE
APVD
M.PERCHEKKE

21FEB05
21FEB05
-

DIMENSIONS:
INCHES

0 PLC ±
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.0020
ANGLES ±2°
FINISH

TOLERANCES UNLESS OTHERWISE SPECIFIED:

PRODUCT SPEC
108-1973
APPLICATION SPEC
114-13038
WEIGHT
CUSTOMER DRAWING

NAME
RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL

SIZE
A100779

CAGE CODE
C=6450170

DRAWING NO
REV
J5

TE Connectivity

SCALE
4:1

SHEET
7



OF
13

REV
J5

LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER		SIGNAL				POWER		
			P4	P3	4	3	2	1	P2	P1	
3-6450170-1	D		RM	RA	H	H	H	H	RA	RM	
	C				G	G	G	G			
	B				E	E	E	E			
	A	HD			F	F	F	F			
2P + 16S + 2P											

PART NUMBER	ROWS		POWER			SIGNAL						POWER				
			P7	P6	P5	6	5	4	3	2	1	P4	P3	P2	P1	
1-6450170-8	D		RM	RM	RA	H	H	H	H	H	H	RM	RM	RM	RM	
	C					G	G	G	G	G	G					
	B					F	F	F	F	F	F					
	A					E	E	E	E	E	E					
4P + 24S + 3ACP																



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN: R. GRZYBOWSKI 21FEB05
CHK: M. PERCHERKE 21FEB05
APVD: M. PERCHERKE

DIMENSIONS:
INCHES

0 PLC ±
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.0020
ANGLES ±2°
FINISH

TOLERANCES UNLESS OTHERWISE SPECIFIED:

108-1973
APPLICATION SPEC
114-13038

MATERIAL

CUSTOMER DRAWING

NAME: RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL


SIZE: A1
CAGE CODE: 100779
DRAWING NO: C=6450170


RESTRICTED TO: -

TE Connectivity



SCALE: 4:1
SHEET: 8 OF 13
REV: J5



PART NUMBER	ROWS		POWER		SIGNAL			POWER				
			P6	P5	3	2	1	P4	P3	P2	P1	
3-6450170-3	D C B A	 HD			H G F E	H G F E	H G F E					
4ACP + 12S + 2P												



THIS DRAWING IS A CONTROLLED DOCUMENT.						DWN	R. GRZYBOWSKI	21FEBO05			
						CWK	M. PERCZERKE	21FEBO05			
						APVD	M. PERCZERKE	-	TE Connectivity		
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:				NAME		RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL			
INCHES		0 P/LC ±. 1 P/LC ±. 2 P/LC ±.01 3 P/LC ±.005 4 P/LC ±.0020 <i>±.002</i> ANGLES				PRODUCT SPEC					
						108-1973					
						APPLICATION SPEC					
						114-13038					
MATERIAL		FINISH		WEIGHT		SIZE		CAGE CODE		DRAWING NO	
-		-		-		A1		00779		C=6450170	
										RESTRICTED TO	
						CUSTOMER DRAWING		SCALE		REV J5	
								4:1		SHEET 9 OF 13	


LOC		DIST		REVISIONS				
ES	00	P	LTR	DESCRIPTION		DATE	DWN	APVD
		-		SEE SHEET 1		-	-	-

PART NUMBER	ROWS		POWER		SIGNAL		POWER		
			P4	P3	2	1	P2	P1	
3-6450170-5	D C B A		RA	RA	H	H	RM	RM	
					G	G			
					F	F			
					E	E			
					2P + 8S + 2P				




THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. GRZYBOWSKI CHK M. PERCHERKE APVD M. PERCHERKE	21FEB05 21FEB05 -
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±.01 1 PLC ±.01 2 PLC ±.01 3 PLC ±.005 4 PLC ±.0020 ANGLES ±.2° FINISH	PRODUCT SPEC 108-1973 APPLICATION SPEC 114-13038 WEIGHT	NAME RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL
MATERIAL		CAGE CODE DRAWING NO. 100779	RESTRICTED TO J5
CUSTOMER DRAWING		SCALE 4:1	SHEET 10 OF 13

PART NUMBER	ROWS		POWER	SIGNAL								POWER	
			P2	8	7	6	5	4	3	2	1	P1	
3-6450170-7	D C B A		 RM	H	H	H	H	H	H	H	H	 RM	
				G	G	G	G	G	G	G	G		
				F	F	F	F	F	F	F	F		
				E	E	E	E	E	E	E	E		
IP + 32S + IP													

4805 (3/11)

PART NUMBER	ROWS		POWER		SIGNAL		POWER			
			P5	P4	2	1	P3	P2	P1	
3-6450170-9	D C B A				H	H				
					G	G				
					F	F				
					E	E				
3ACP + 8S + 2P										



TE RECOMMENDED PCB LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWA R. GRZYBOWSKI		ZIFEB05		 TE Connectivity	
		CMP M. PERCHERKE		ZIFEB05			
DIMENSIONS: INCHES		TOLERANCES, UNLESS OTHERWISE SPECIFIED:		NAME		RIGHT ANGLE RECEPTACLE ASSEMBLY WITH GUIDES MULTI-BEAM XL	
		0 PLC ± 2 PLC ± 3 PLC ±.005 4 PLC ±.0020 ANGLES FINGER		PRODUCT SPEC 108-1973 APPLICATION SPEC 114-13038 WEIGHT			
		CASE CODE 100779		DRAWING NO C-6450170		RESTRICTED TO -	
MATERIAL				CUSTOMER DRAWING		SCALE 4:1	
						SHEET 12 OF 13	
						REV J5	



LOC	DIST	REVISIONS					
ES	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		POWER				SIGNAL			POWER							
			P10	P9	P8	P7	3	2	1	P6	P5	P4	P3	P2	P1		
4-6450170-0	D		RM	RM	RM	RM	H	H	H	RM	RM	RM	RM	RA	RA		
	G						G	G									
	F						F	F									
	E						E	E									
		HD															HD
6P + 12S + 4P																	

PART NUMBER	ROWS		POWER						SIGNAL						POWER		
			P8	P7	P6	P5	P4	P3	6	5	4	3	2	1	P2	P1	
4-6450170-1	D		RM		RM		RA		H	H	H	H	H		RM	RM	
	C								G	G	G	G	G				
	B								F	F	F	F	F				
	A								E	E	E	E	E				
2P + 24S + 6P																	

NO CONTACTS LOADED

NO CONTACTS LOADED



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN R.GRZYBOWSKI 21FEB05
CHK M.PERCHERKE 21FEB05
APVD M.PERCHERKE

NAME

DIMENSIONS:
INCHES

0 PLC ±"
1 PLC ±.01
2 PLC ±.01
3 PLC ±.005
4 PLC ±.0020
ANGLES ±2°
FINISH

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

PRODUCT SPEC
108-1973
APPLICATION SPEC
114-13038
WEIGHT

CUSTOMER DRAWING

TE Connectivity

RIGHT ANGLE RECEPTACLE ASSEMBLY
WITH GUIDES
MULTI-BEAM XL

SIZE A100779
CAGE CODE
DRAWING NO C=6450170
SHEET 13 OF 13
REV J5