




LOC		DIST		REVISIONS					
—		—		P	LTR	DESCRIPTION	DATE	DWN	APVD
					AA	REV PER ECO 15-016064	11-9-15	CT	CD



1. THIS RECEPTACLE WILL MATE WITH ANY PLUG CONNECTOR WITH THE SAME INSERT ARRANGEMENT AS DEFINED BY MS18273-2.
 2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS RECEPTACLE IS .054 DIA.
 3. BE. CU. RETENTION CLIPS ARE INCLUDED IN INSERTS.
- △ CUSTOMER PART NUMBER MAY BE SPLIT BETWEEN FRONT AND REAR SHELL, SAME SIDE.
- △ UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
- △ INSPECTION REQUIREMENTS PER R4383.
- △ CONNECTOR SUPPLIED WITH 17 CONTACTS, AMP PART NUMBER 206071-1. INSPECTION REQUIREMENTS PER R4383.
- △ CONNECTOR SUPPLIED WITH 25 CONTACTS, AMP PART NUMBER 206071-1. INSPECTION REQUIREMENTS PER R4383.
- △ THESE CONNECTORS ARE QUALIFIED TO GODDARD SPACE FLIGHT CENTER SPECIFICATIONS S-311-P-4.
- △ 10 RESTRICTED TO CAE ELECTRONICS ONLY.



AMP P/N 206071-1
GSFC P/N G-08-S1
(SUPPLIED WITH 206064-6 AND 206064-7 ONLY)

.120		570566-1	1-206499-0	1-206499-0
.154	△ 10 △ 9	311P407-1S-B-15	206499-1	206499-9
.120	△ 10 △ 9	311P407-1S-B-12	206499-4	206499-8
.120	△ 8	20025720P1015S	206499-7	206499-7
.120	△ 7	R4383 P15S	206499-6	206499-6
.120	△ 6	R4383 P15S-2	206499-5	206499-5
.120	△ 9	311P407-1S-B-12	206499-4	206499-4
.154		----	206499-3	206499-3
.120		R9259P15S	206499-2	206499-2
.154	△ 9	311P407-1S-B-15	206499-1	206499-1
Ø A	REMARKS	CUSTOMER P/N	MARKED AMP P/N	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M (ISO STANDARDS)		DWN P. YEAGER 020CT2006	TE Connectivity	
DIMENSIONS: INCHES		CHK D. MILLER 050CT06	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. MILLER 050CT06	PRODUCT SPEC	
0 PLC ± .		APPLICATION SPEC		SIZE CAGE CODE DRAWING NO
1 PLC ± .		WEIGHT		
2 PLC ± .		CUSTOMER DRAWING		SCALE 4:1
3 PLC ± .005		SHEET 1 OF 1		REV AA
4 PLC ± .		RESTRICTED TO		
ANGLES ± .		MATERIAL SEE CALLOUTS		
FINISH SEE CALLOUTS		A1 00779 C=206499		