

## Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number : 342A1XX-25/225 Description: Transition, 45°

1. All dimensions are in  $\frac{\text{Incres}}{[\text{millimeters}]}$ 

- 2. Dimensions appearing in table are as follows:
  - a As Supplied
  - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated ports. When coating is added, entry diameters will be reduced by .06 max.





AS SUPPLIED

TABLE OF DIMENSIONS											
PART NUMBER	Н		J & K		Р	R	s	HW	JW & KW		
	Min	Max	Min	Max	±10%	±10%	±10%	±20%	±20%		
	a	ь	a	b	b	b	b	ь	b		
342A112-25/225	.52 [13,2]	.24 [6,1]	.26 [6,6]	.12 [3.0]	1.76 [44.7]	.90 [22,9]	.84 [21,3]	.06 [1,52]	<u>.04</u> [1,02]		
342A124-25/225	1.06 [26,9]	.49 [12,4]	.52 [13,2]	<u>.24</u> [6,1]	3.54 [89,9]	1.66 [42,2]	1.68 [42,7]	.10 [2,54]	<u>.06</u> [1,52]		
342A138-25/225	2.19 [55,6]	1.00 [25,4]	1.06 [26,9]	.49 [12,4]	7.21 [183,1]	3.76 [95,5]	3.40 [86,4]	.18 [4,57]	<u>.10</u> [2,54]		

## Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision : A Date: 4/13/95


Part Number : 342A1XX-25/225

Description: Transition, 45°

## Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number : 342A1XX-25/225 Description: Transition, 45°

COMPATABILITY CHART									
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION				
-25	Elastomer, Fluid Resistant	RT-1325	/225	S-1206	Adhesive				



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

## Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision : A Date: 4/13/95 Part Number : 342A1XX-25/225 Description: Transition, 45°

CAD FILE MP95178