

# T-Series

## Single Pole Rocker & Paddle Switches

The predecessor to the Corvette series whose versatility has allowed it to stand the test of time. Traditional styling coupled with self cleaning contacts, integrated wire leads, a multitude of circuits, ratings, and actuator choices has made the TA/LTA-Series appeal to a wide range of markets, including Appliance, HVAC, Food service, Transportation.



**Carling Technologies®**

Innovative Designs. Powerful Solutions.

Innovative Designs. Powerful Solutions.

Carling Technologies, Inc.  
60 Johnson Avenue • Plainville, CT 06062-1177  
Phone: (860) 793-9281 • Fax: (860) 793-9231  
Email: [sales@carlingtech.com](mailto:sales@carlingtech.com) • [www.carlingtech.com](http://www.carlingtech.com)

## Dielectric Strength

UL/CSA:  
1000V - live to dead metal parts

## Electrical Life


100,000 cycles

## Mechanical Life

100,000 cycles

## Operating Temperature

32°F to 185°F (0°C to 85°C)



### 1 BASE PART NUMBER: SERIES/CIRCUITRY/RATING<sup>4</sup>/TERMINATION

10A 250 VAC, 15A 125 VAC, 3/4 HP 125-250 VAC

Solder Lugs      .250 Tabs      Wire Leads

**Standard Base**  
ON-NONE-OFF      TA200      TA201      TA205  
ON-NONE-ON      TB200      TB201      TB205  
ON-OFF-ON      TC200      TC201      TC205

**5A 250 VAC, 10A 125 VAC, 1/2 HP 125-250 VAC**  
(ON)-NONE-OFF      TA10A      TA10B      TA10F  
(ON)-NONE-(OFF)      TA10L      TA10M      TA10T  
(ON)-NONE-(ON)      TB10A      TB10B      TB10F

### T-SERIES W/ PLUNGER ACTUATOR<sup>1,2</sup>

10A 250 VAC, 16A 125 VAC, 1/2 HP 125-250 VAC  
OFF-NONE-(ON)      -      TA25B-PLB-B      TA25F-PLB-B  
ON-NONE-(OFF)      -      -      TA25T-PLB-B

### T SERIES W/ MOMENTARY ROCKER ACTUATOR

10A 250 VAC, 15A 125 VAC, 20A 125-250 VAC "H", 3/4 HP 125-250 VAC  
(ON)-NONE-OFF      -      TA22B-TLB-B      -  
(ON)-NONE-(OFF)      -      TA22M-TLB-B      -

### 2 ACTUATOR STYLE

T Rocker      PS Short Paddle  
P Paddle

### 3 ACTUATOR COLOR<sup>5</sup>

B Black      W White

### 4 BEZEL COLOR<sup>5</sup>

B Black      W White

Notes:  
Imprinting is available. Consult factory.

- Optional plunger support option is available for applications requiring extensive lateral travel, consult factory for details.
- Maintained circuit not available with TA22 and TA25 Series.
- .187 tab terminals also available. Consult factory for catalog number callout.
- Additional ratings are available. Consult factory.
- Additional colors are available. Consult factory.
- ( ) Indicates momentary function.

