





NOTES:

1. MADE FROM HIGH COPPER CONTENT ALLOY. FURNISHED WITH FULL THREADED SILICON BOLT, NUTS, AND LOCKWASHERS.
2. THESE CONNECTORS ARE UL LISTED FOR GROUNDING AND BONDING, AND DIRECT BURIAL APPLICATIONS.
3. PACKAGE QTY: -Q = 25

PANDUIT PART NUMBER	CONDUCTOR RANGE	DIMENSIONS							BOLT D/A.
		A		B		C			
		IN	MM	IN	MM	IN	MM		
		IN	MM	IN	MM	IN	MM		
GM-2-Q	4 SOL. - 2/0 STR	1.63	41	1.13	28	1.75	44	0.38	
GM-3-Q	2/0 STR - 250 kcmil	1.88	47	1.50	38	2.00	51	0.50	

REV	DATE	BY	CHK	DESCRIPTION	ECN	SCALE	N/A	DRAWING NO / CAD FILE	C41169_02
02	10/08	JHNU	JHNU	REVISED UL LISTING CONVERTED DWG. TO SOLIDWORKS					
01	1/01	EJS		DIM A FOR PART GM-3-Q WAS 2.13; ADDED PACKAGE CODE TO PART NUMBER, ADDED NOTE 3, REVISED UL LISTING, FILE SPEC WAS N41169CA_PCD_00					
00	10/95	ED	WJB	DWG. RELEASED	03702				