


NOTE:
 64 THR'D P.I.
 MAJOR .1875-.0028
 PITCH .1799-.0024
 MINCR .1708

JKL LAMP NUMBER	VOLTS RATED	AMPS $\pm 10\%$	MSCP $\pm 25\%$	LUMENS $\pm 25\%$	AVERAGE LIFE HRS.	FILAMENT TYPE
329	2.5	.400	.500	6.91	30	C-2R
325	3.0	.190	.250	3.14	350	C-2R
8662	6.0	.040	.030	0.38	1,000	C-2R
8552	6.3	.200	.550	6.91	5,000	C-2F
8635	28.0	.040	.340	4.27	2,800	C-2R

METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		JKL COMPONENTS CORPORATION TITLE T-1 1/4 SPECIAL MIDGET SCREW BASE			
DRAWN BY L. WENGSTROM	APPV'D BY QC	DATE 9/26/06	SIZE A	FSCM NO. 55335	DRAWING NO. SCREW BASE SPECIAL T-1 1/4		
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 10/11/00	REVISION DATE 9/26/06	REV. NO. A SHEET 1 OF 1	

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
A	CHNG. FILAMENT TYPE FOR 325 TO C-2R RELEASE & CANCEL 3515, 8645	9/26/06 10/11/00