



- 1 MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK PLUG
- 2 RECOMMENDED PANEL THICKNESS 0.76 - 2.29 mm
- 3 PANEL MUST BE PUNCHED SO THAT THE HOUSING ENTERS THE PANEL IN THE SAME DIRECTION AS THE PUNCH
- 4 CIRCUIT NUMBER 1 LOCATION
- 5 DIMENSION INDICATED AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR
- 6 UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE EACH ON SIDE OF HOUSING
- 7 MATERIAL CORRESPONDING TO THE REQUIREMENTS OF IEC 60335 (INCL. GLOW WIRE TEST 750°C, WITHOUT FLAME)
- 8 OPTIONAL FOR KEYING HOUSING IN PANEL
- 9 PRELIMINARY PART NOT RELEASED FOR PRODUCTION

7	1-1703062-2	A	PA66 UL94 V0 (GW T 750 °C)	NATURAL
9	1-1703062-1	1	PA6 UL94 V0	NATURAL
7	1703062-4	A	PA6 UL94 V2 GW T 750 °C	BLACK
7	1703062-3	A	PA6 UL94 V2 GW T 750 °C	RED
7	1703062-2	A	PA6 UL94 V2 GW T 750 °C	BLUE
7	1703062-1	A	PA6 UL94 V2 GW T 750 °C	NATURAL
REMARK		PN	REV	MATERIAL
				COLOUR

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN MAHNKE, B.	16APR2004		 TE Connectivity					
		CHK ZITZ, A.	26APR2004							
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD BLEICHER, M.	NAME					
		PRODUCT SPEC		CAP 2 CIRCUIT UNIVERSAL MATE-N-LOK						
		-		-						
		APPLICATION SPEC		-						
		-								
MATERIAL		FINISH		WEIGHT	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO		
PA 6				2.55 g	A2	00779	C=1703062	-		
CUSTOMER DRAWING					SCALE	4:1	SHEET	1 OF 1	REV	B5