







All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor.
Property of FCI. Copyright FCI.



LAY-OUT
P.C.B.- HOLE



PERFORMANCE CHARACTERISTICS

CURRENT RATING: 1.5 A AT 20°C (FULLY LOADED)
1 A AT 70°C (FULLY LOADED)

RATED VOLTAGE:500 V AC (CONT /CONT)

OPERATING TEMPERATURE : -55°C TO 125°C

CONTACT RESISTANCE :20 mΩ MAX

INSERTION FORCE: 0.75N MAX/CONT

EXTRACTION FORCE : 0.15N MIN /CONT

INSULATION RESISTANCE: $10^4 \text{ M}\Omega$ MIN

NOTES

NOTES LEAD FREE INDICATOR :LF=LEAD FREE

1.  PERFORMANCE LEVEL INDICATION
(REF DWG NO.BS.C.201844.003)
2. THIS PRODUCT IS CSA APPROVED.
THIS PRODUCT IS UL RECOGNIZED.
- 3.FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING :BS.A.201572.001
- 4.THIS PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

rev	ecn no	dr	date
A	CONVERSION REVISION 06	KN	14-09-0
B	DG05-0381	Kason	10-10-0
C	DG07-0362	Kason	05-09-0
D	DG10-0110	NZ	05-30-0
-	-	-	-
-	-	-	-
06	BEC9.3546	R.M.	110601

Material			Spec ref				
Mat code			✓	tolerance	projection	MM	
Heatreat				1DEC+0.2 1DEC 2DEC+0.10 2DEC ANGLES+1*HDEREN			
Plating/Finish							
Dr	W.Panis	070492				size A4	Scale 1:500
Eng			Product family MILLIPICS				
Chr			Model Name			ECN	
Appr			Model Revision			REL Level	
		title RIGHT ANGLE RECEPTACLE CONNECTOR /TYPE M			dwg no BS,C ,201444,005		Rev. D
Pro/E file	catalog no		HM2R05PA5101----		Customer		sheet 1 of 1