




chain of balls stretched length with loop 84mm

All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

IEC 60169-17, MIL-PRF-39012, DIN EN 122200

Documents

N/A

Material and plating

Connector parts

Coupling nut
Rivet
Cover plate
Chain of balls
Loop
Gasket

Material

Brass
Brass
Brass
Brass
Brass
Foam rubber

Plating

Flash white bronze over silver(e.g. Optargen®)
Flash white bronze over silver(e.g. Optargen®)
White bronze(e.g. Optalloy®)
Flash white bronze over silver(e.g. Optargen®)
Flash white bronze over silver(e.g. Optargen®)

TECHNICAL DATA SHEET

Rosenberger

TNC 50 Ω PROTECTION CAP
PLUG WITH CHAIN

56Z112-000N

Electrical data

N/A

Mechanical data

Mating cycles min. 500

Environmental data

Temperature range -65°C to +165°C
Thermal shock MIL-STD-202, Meth. 107, Cond. B
Corrosion MIL-STD-202, Meth. 101, Cond. B
Vibration MIL-STD-202, Meth. 204, Cond. B
Shock MIL-STD-202, Meth. 213, Cond. G
Moisture resistance MIL-STD-202, Meth. 106
Degree of protection (mated pair) IEC 60529, IP63
RoHS compliant

Tooling

N/A

Suitable cables

N/A

Weight

Weight 10.4 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	10/08/04	Sa. Krautenbacher	20.03.14	d00	14-0352	T. Krojer	20.03.14
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de		Page 2 / 2