Product datasheet Characteristics

9007C62BY247



- П/Л	21	
- 171		
	_	-

Main	
Range of product	9007
Series name	Heavy duty
Device short name	С
Head type	Turret head rotary lever
Type of operator	Spring return lever arm (standard pre-travel) (to be ordered separately Drive shaft (reduced diameter to 0.306 in) lever arm
Switch actuation	CW
Cable entry	NPT conduit entry, cable outer diameter: 0.5 in
Contacts type and composition	2 NO/2 NC
Contact operation	Snap action

Complementary

complementary	
Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form ZZ
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	4 lbf.in
Tripping angle	4 °
Maximum displacement angle	90 °
[le] rated operational current	10 A, Q600 10 A, A600
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	<= 600 V
Local signalling	Without pilot light
Product certifications	CE CSA UL listed
Provided equipment	Receptacle
Environment ambient air temperature for operation Offer Sustainability	-20185 °F
Not Green Premium product	Not Green Premium product
Will not be Compliant	Will not be Compliant
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov





