



C	Wire _____ Tinned copper
	Gauge _____ AWG 28/7 0,089 mm ²
	Voltage rating _____ 300 Vr.m.s
	Current rating _____ 2,1A at 25°C
	Capacity unbalanced _____ 45,9 pF/m at 1 MHz
	Impedance unbalanced _____ 105 Ω
	Propagation delay _____ 4,9 ns/m nominal
	Insulation material _____ PVC
B	Temperature rating _____ -20°C (operating) -30°C (static) to +105°C
	Flammability rating _____ Flame retardant VW1
	Insulation resistance _____ 100 MΩ/km
	Approval _____ UL AWM style 2651

A					Dat.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 flat cable 16 poles	Maßstab/ Scale	
					Detail.	20/10/05			JMDR	10:1
					Insp.					
		EC01360	19/02/10	SC	Stand.					
	09 18 016 7004	100 m (328 feet)	34400	17/09/07	PK	HARTING EURL F-95972 Paris		TB 09 18 016 700X	Blatt/ Page	
	09 18 016 7001	30,48 m (100 feet)	33246	20/10/05	JMDR				1 / 1	
	Part number	Length per reel	Mod.	Dat.	Name				Sub.	