



Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Eco-Surge 7-Outlet Surge Protector, 6-ft. Cord, 1080 Joules, Individually-Controlled

MODEL NUMBER: TLP76MSG









Description

Tripp Lite's TLP76MSG offers reliable, GREEN surge technology that protects your computer and peripherals as well as the environment and your wallet. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. The TLP76MSG has one always on outlet for those peripherals that need constant power like a fax machine, DVR or router. It also offer convenient, individual outlet switches that allow users to select which device is turned on and off. The TLP76MSG has 7 total outlets, 6 foot cord and diagnostic LEDs to warn of wiring problems and suppressor damage. Network-grade AC suppression rated at 1080 joules shields equipment from surges and line noise. Designed with an attractive cool gray suppressor housing, the TLP76MSG can accommodate up to 4 transformer plug outlets offering convenient protection of desktop computer equipment and accessories. \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- Energy-saving green outlets allow individual outlet control using illuminated power switches for cutting power to peripherals not in use.
- Six green outlets have their own illuminated ON/OFF switch for cutting power to peripherals when they
 are not in use. One "Always On" outlet provides continuous power for devices such as DVRs (TiVo),
 cable and satellite boxes, modems, routers and fax machines.
- In addition to the individual illuminated outlet switches, an illuminated Master Switch controls power to
 all outlets (except the Always On outlet) at once. It can override other "ON" settings to cut power to all
 switched outlets at once.
- Protected (Green) LED assures protection is present & Always On (Red) LED indicates that the Always
 On outlet is receiving power.
- 1080 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their

Highlights

- · Individual outlet control
- 1080 joules
- 7 outlet / 6-ft cord
- Diagnostic LEDs
- \$25,000 <u>Ultimate Lifetime</u>
 <u>Insurance</u> (U.S., Canada, and Puerto Rico only)

Package Includes

- TLP76MSG ECO-SURGE
 Home/Business Theater Surge
 Suppressor
- Instruction manual with warranty information



peak (sharper, crisper video; deeper, fuller audio and longer component life spans).

• Automatic shutoff cuts power to outlets when the protection circuit has been compromised

Specifications

OUTPUT		
Output Volt Amp Capacity (VA)	120	
Output Watt Capacity (Watts)	1800	
Frequency Compatibility	60 Hz	
Output Receptacles	(7) 5-15R	
Transformer Accommodation	Supports 1 large transformer without covering remaining outlets, accepts up to 4 transformers total	
Right-Angle Outlets	0	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMAP - NEMA5-15P	
Input Cord Length (ft.)	6	
Input Cord Length (m)	1.83	
Input Cord Gauge Type	14 AWG, 3 COND, SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	72000	
Right-Angle Plug	0	
USER INTERFACE, ALERTS & CONTROLS		
Switches	1 x Lighted Master Switch & 6 x Lighted Receptacle Switches	
LED Indicators	Protected (Green)" & Always On Receptacle (Red)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1080	
AC Suppression Response Time	<1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression.	
Clamping Voltage (RMS)	150	
UL1449 Let Through Rating	400v	
EMI / RFI Filtering	Up to 40dB	



DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	0	
Cable (Coax) Protection	0	
Network (Ethernet) Protection	0	
PHYSICAL		
Shipping Dimensions (hwd / in.)	17.2 x 4.24 x 2	
Shipping Dimensions (hwd / cm)	43.69 x 10.77 x 5.08	
Shipping Weight (lbs.)	1.76	
Shipping Weight (kg)	0.80	
Unit Dimensions (hwd / in.)	1.40 x 3.40 x 15	
Unit Dimensions (hwd / cm)	3.56 x 8.64 x 38.1	
Unit Weight (lbs.)	1.54	
Unit Weight (kg)	0.70	
Material of Construction	Plastic	
Integrated Keyhole Mounting Tabs	Keyhole mounting slots enable wall mounting	
Color (AC Line Cord)	Cool Gray	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 <u>Ultimate Lifetime Insurance</u>	

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies