

"Stay Connected" with




HEYware Products

a PennEngineering® Company


## Heyco® Nylon PCB Supports - Screw and Lock

▼ ALL NEW PRODUCTS! ▼




BAYONET SNAP LOCK 10,2 /  
6-32 SELF-TAPPING SCREW

**HHCBS**




BAYONET SNAP LOCK 10,2 /  
M4 THREADED FEMALE

**HLCBS-TF-M4**



BAYONET SNAP LOCK 10,2 /  
6-32 THREADED FEMALE

**HLCBS-TF-632**



BAYONET SNAP FIT 10,2 /  
6-32 THREADED FEMALE

**HCBS-TF-632**

|         |      | Maximum Thickness* |     | Mounting Hole Diameter |     | Maximum Thickness |     | Mounting Hole Diameter |     | Maximum Thickness |     | Mounting Hole Diameter |     | Maximum Thickness |     | Mounting Hole Diameter |     |
|---------|------|--------------------|-----|------------------------|-----|-------------------|-----|------------------------|-----|-------------------|-----|------------------------|-----|-------------------|-----|------------------------|-----|
|         |      | in.                | mm. | in.                    | mm. | in.               | mm. | in.                    | mm. | in.               | mm. | in.                    | mm. | in.               | mm. | in.                    | mm. |
| PCB     |      | .062               | 1,6 | .157                   | 4,0 | .062              | 1,6 | .157                   | 4,0 | .062              | 1,6 | .157                   | 4,0 | .062              | 1,6 | .157                   | 4,0 |
| Chassis |      | .312               | 7,9 | 6-32                   |     | threaded          |     |                        | M4  | threaded          |     | 6-32                   |     | threaded          |     | 6-32                   |     |
| A       |      | PART NO.           |     | DESCRIPTION            |     | PART NO.          |     | DESCRIPTION            |     | PART NO.          |     | DESCRIPTION            |     | PART NO.          |     | DESCRIPTION            |     |
| in.     | mm.  | Natural            |     |                        |     | Natural**         |     |                        |     | Natural**         |     |                        |     | Natural**         |     |                        |     |
| .250    | 6,4  | 10616              |     | HHCBS-04 †             |     |                   |     |                        |     |                   |     |                        |     |                   |     |                        |     |
| .375    | 9,5  | 10617              |     | HHCBS-06               |     | 10829             |     | HLCBS-TF-M4-06         |     | 10890             |     | HLCBS-TF-632-06        |     | 10897             |     | HCBS-TF-632-06         |     |
| .500    | 12,7 | 10618              |     | HHCBS-08               |     | 10830             |     | HLCBS-TF-M4-08         |     | 10891             |     | HLCBS-TF-632-08        |     | 10898             |     | HCBS-TF-632-08         |     |
| .625    | 15,9 | 10619              |     | HHCBS-10               |     | 10831             |     | HLCBS-TF-M4-10         |     | 10892             |     | HLCBS-TF-632-10        |     | 10899             |     | HCBS-TF-632-10         |     |
| .750    | 19,1 | 10620              |     | HHCBS-12               |     | 10832             |     | HLCBS-TF-M4-12         |     | 10893             |     | HLCBS-TF-632-12        |     | 10900             |     | HCBS-TF-632-12         |     |
| .875    | 22,2 | 10621              |     | HHCBS-14               |     | 10833             |     | HLCBS-TF-M4-14         |     | 10894             |     | HLCBS-TF-632-14        |     | 10901             |     | HCBS-TF-632-14         |     |
| 1.000   | 25,4 | 10622              |     | HHCBS-16               |     | 10834             |     | HLCBS-TF-M4-16         |     | 10895             |     | HLCBS-TF-632-16        |     | 10902             |     | HCBS-TF-632-16         |     |
| 1.125   | 28,6 | 10623              |     | HHCBS-18               |     |                   |     |                        |     |                   |     |                        |     |                   |     |                        |     |
| 1.250   | 31,8 | 10624              |     | HHCBS-20               |     |                   |     |                        |     |                   |     |                        |     |                   |     |                        |     |
| 1.406   | 35,7 | 10625              |     | HHCBS-22.5             |     |                   |     |                        |     |                   |     |                        |     |                   |     |                        |     |

Standard color natural. For special order parts in UL 94V-0 natural material, add the suffix "F" to Part No.

\*Refers to thread depth at chassis which is .312" (7,9 mm)

\*\*Consult Heyco for HLCBS-TF in V-0 material

†Thread depth is .20" (5,2 mm)

Quick  
Specs

Material Nylon 6/6  
Flammability Rating 94V-2  
Temperature Range -40°F (-40°C) to 185°F (85°C)