

## SENCITY® Omni-S Cellular/LTE 800 Antenna 1399.17.0245

### Description

Omni - directional Cellular/4G LTE 800 SISO antenna  
 Rugged and low profile cabinet and pole/wall mount antenna  
 Supporting mobile bands LTE 790 to 960 MHz, Cellular 1710 to 2170 and  
 LTE 2300, 2500, 2600 MHz bands  
 Single hole cabinet or wall/pole mounting  
 For outdoor and indoor applications  
 Ingress protection IP66 / IP67 (IP69k)



### Product Configuration

### Technical Data

#### Electrical Data

	Band 1	Band 2	Band 3	Band 4
Frequency (MHz)	790 - 930	930 - 960	1710 - 2170	2300 - 2690
VSWR	1.8	2.5	1.9	1.6
Impedance (Ohm)	50	50	50	50
Gain (dBi)	2	2	6	4
Composite power max (W)	60	60	50	40
Ambient temperature (°C)	25	25	25	25

#### Ports

	Port 1
Connector	N, jack (female)
Cable Type	ENVIROFLEX_316_D
Cable Length (m)	1
Min. radius static (mm)	5
Min. radius dynamic (mm)	30
Polarization	vertical
DC grounded	No

#### Connections

	Band 1	Band 2	Band 3	Band 4
Port 1	X	X	X	X

#### General Data

GROUND PLANE: Antenna works on metallic as well as on non-metallic ground plane. VSWR is valid for both mounting options  
 GAIN VALUES: Indicated gain values are valid for non-metallic ground plane. Gain of this antenna on metallic surface is higher for 790 to 960 MHz: 4 dBi (instead of 2 dBi)

#### INGRESS PROTECTION:

- IP 66, IP67 AND IP 69K when mounted on cabinet's flat surface or roof
- IP 66 and IP67 when mounted on bracket with sealed cable conduit

#### Mechanical Data

Dimensions (mm) 33.2 x 145 (Height x Diameter)  
 Weight (kg) 0.3

## SENCITY® Omni-S Cellular/LTE 800 Antenna 1399.17.0245

### Environmental Data

Environmental conditions	indoor/outdoor
Operation temperature (°C)	-55 to 85
Storage temperature (°C)	-55 to 85
Transport temperature (°C)	-55 to 85
Flammability rating	UL 94-V0
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
Lead-free soldered	yes
WEEE 2012/19/EU	special marking needed
REACH 1907/2006/EC	compliant

TEMPERATURE RANGE: EN 60068-2-1 (2007), test Ab, -55°C, 16h and EN-60068-2-2 (2007), test Bb, +85°C, 16h

THERMAL SHOCK: IEC 60068-2-14 (2009), test Na, -55°C to +85°C, 3h, 5 cycles

SOLAR RADIATION: EN 60068-2-5, test Sa, procedure B, 1200 W/m<sup>2</sup>, 3 x 24h

RELATIVE HUMIDITY: EN 60068-2-78 (2012), test Cb, RH 95%, 21d (damp heat, steady state)

RELATIVE HUMIDITY: EN 60068-2-30 (2005), RH 97%, 6 cycles (damp heat, cyclic)

SALT SPRAY: EN 60068-2-11 (2002), test Ka, 96h

MECHANICAL VIBRATION / SHOCK: IEC 61373 (1999), § 9 and § 10, category 2

VANDALISM: EN 60068-2-75 (1997), IEC 62262 (2002) IK10, test Ehc

CORROSION: MIL-F-14072 E type 1 "exposed"

### Material Data

Radome colour	RAL 9010 (white)
Radome material	PC (Polycarbonate)

### Related Products

9091.99.0259 Bracket kit for SENCITY® Omni-S MIMO antenna

Accessory kit 9091.99.0259 is available via H+S customizing process, no item number as extra deliverable assigned yet.

### Related Documents

Mounting instruction	DOC-0000711826
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00328358
3D-model	DOC-0000777873

### Additional Information

This product can be customized alternatively in the following way: - Cable length from 300 to 5000 mm - Choice of RF connector (SMA, R-SMA, QMA, TNC, R-TNC, N) - Customer specific port labeling on pigtails - Further wireless bands, e.g. dual-band WiFi MIMO or Cellular/LTE SISO with GNSS

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[1399.17.0245](#)