


LOC	DIST	REVISIONS					
DF	X0	P	LTR	DESCRIPTION	DATE	DWN	APVD
			0	RELEASED	9-02	JMK	JL

AS SHIPPED TO CUSTOMER

Technical drawing of a cable connector assembly. The drawing shows a cross-section of the assembly with the following dimensions and labels:

- Overall length: 1.125 [28.58] MAX
- Cap height: .670 ± .020 [17.02 ± 0.51]
- Cap to ferrule distance: .535 ± .020 [13.59 ± 0.51]
- Labels: CAP, HOUSING, FERRULE, COUPLING NUT, .312 [7.92] HEX, CENTER CONTACT DIELECTRIC GASKET, RETAINING RING, CABLE (CUSTOMER SUPPLIED)

ASSEMBLED VIEW

DESIGNED TO USE RG-178/U OR EQUIVALENT		THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. KAISER 9/24/02		1052179-1	
CABLE ENTRY DIAMETER MIN		DIMENSIONS: INCHES [mm]		CHK J. LIPPERT 10-18-02		PART NO.	
HOUSING: .037 [0.94]				APVD J. LIPPERT 10-18-02		NAME	
CONTACT SLOT: .041 [1.04]				PRODUCT SPEC		SMA RIGHT ANGLE CABLE PLUG-SOLDER ATTACHMENT (M39012/56-3106) CAT A	
— —				APPLICATION SPEC		SIZE	
— —				FINISH		CAGE CODE	
FERRULE: .099 [2.51]		MATERIAL SEE TABLE		WEIGHT TBD		DRAWING NO	
				CUSTOMER DRAWING		RESTRICTED TO	
						—	
						SCALE 5:1	
						SHEET 1 OF 1	
						REV 0	