




LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
A1	2		B2	ECR-13-016227	11NOV2013	KKB	R.P
			B3	ECR-13-018957	13DEC2013	KKB	RRP
			B4	REVISED PER ECR-14-012053	28AUG2014	AV	KD
			B5	REVISED PER ECR-15-002456	03MAR2015	AV	DZ

D




C




B

- 1
- MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK CAP OR HEADER
- 2
- SMALL NICKS ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE INITIAL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS. NO INDIVIDUAL NICKED TOWER SHALL INCREASE THIS FORCE BY OVER 5.5 NEWTONS.
- 3
- DIMENSION INDICATED IS AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR
- 4
- UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE ON ANY SIDE OF HOUSING
- 5
- POSITION #1 LOCATOR FEATURE MAY BE ROUND OR OBLONG (AS DEPICTED)
- 6
- MATERIAL CORRESPONDING TO THE REQUIREMENTS OF IEC 60335 (INCL. GLOW WIRE TEST 750 ° C, WITHOUT FLAME)
- 7
- PRELIMINARY PART NOT RELEASED FOR PRODUCTION
- 8
- NO LATCH WINDOW PRESENT.
- 9
- LATCH WINDOW PRESENT.


A



1-1703061-3



6/9	1-1703061-3	1	PA66 UL94 V0 GW T 750 °C	NATURAL
6/8	1-1703061-2	A	PA66 UL94 V0 GW T 750 °C	NATURAL
7/8	1-1703061-1	1	PA6 UL94 V0	NATURAL
6/8	1703061-4	A	PA6 UL94 V2 GW T 750 °C	BLACK
6/8	1703061-3	A	PA6 UL94 V2 GW T 750 °C	RED
6/8	1703061-2	A	PA6 UL94 V2 GW T 750 °C	BLUE
6/8	1703061-1	A	PA6 UL94 V2 GW T 750 °C	NATURAL
REMARK	PN	REV	MATERIAL	COLOUR

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN MAHNKE, B. 17OCT2008 CHK ZITZ, A. 26APR2004 APVD BLEICHER, M. 27APR2004		 TE Connectivity							
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ±0.13 3 PLC ± 4 PLC ± ANGLES ±0°30' FINISH		NAME PLUG, 2 CIRCUIT, UNIVERSAL MATE-N-LOK -							
											
MATERIAL											
SEE TABLE											
		PRODUCT SPEC 108-1031		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO	
		APPLICATION SPEC 114-1010		A2		00779		C-1703061		-	
		WEIGHT 2.422 g									
CUSTOMER DRAWING				SCALE 4:1		SHEET 1 OF 1		REV B5			