

## Strain relief - PDZ/4 - 3040575

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Strain relief, Length: 3 mm, Width: 19.9 mm, Height: 23 mm, Number of positions: 4, Color: black



### Product Features

- The conductor can be fixed using Phoenix Contact cable binders
- The strain relief is snapped into the plug center on the spring-cage plugs or spring-cage couplings



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 0.81 g   |
| Custom tariff number                 | 85389099 |
| Country of origin                    | Poland   |

### Technical data

#### General

|          |       |
|----------|-------|
| Color    | black |
| Material | PA-GF |

#### Dimensions

|        |         |
|--------|---------|
| Width  | 19.9 mm |
| Length | 3 mm    |
| Height | 23 mm   |

### Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141199 |
|------------|----------|

## Strain relief - PDZ/4 - 3040575

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.1 | 27141199 |
| eCl@ss 5.0 | 27141145 |
| eCl@ss 5.1 | 27141145 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141190 |
| eCl@ss 9.0 | 27141190 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC002498 |
| ETIM 5.0 | EC002848 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211812 |
| UNSPSC 7.0901 | 39121411 |
| UNSPSC 11     | 39121411 |
| UNSPSC 12.01  | 39121411 |
| UNSPSC 13.2   | 39121411 |