





REV.	DATE	DESCRIPTION
NC	01/29/07	INITIAL RELEASE



RECOMMENDED
CABLE STRIPPING DIM'S



- NOTE:
1. CRIMPED FERRULE HEX CRIMP SIZE .128"
 2. CONTACT PIN TO SOLDER

8					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020" DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex									
7						DRAWN	G.R.S.	01/29/07											
6						CHECKED			PART DESCRIPTION SSMC CRIMP PLUG (FOR RG-174/U, 188A/U, 316/U)										
5						ISSUED													
4						SHEET	1 OF 1												
3	CONTACT PIN	BER. COPPER	GOLD	1				PART NO.		153100									
2	INSULATOR	TEFLON	NATURAL	1															
1	BODY	BRASS	GOLD	1						DWG. NO.		153100.DWG	REV.	NC	SIZE	A	SCALE	NA	
	DESCRIPTION	MATERIAL	FINISH	QTY				C:/153/153100.DWG											