





PRODUCT NUMBER	PITCH
TRxx15x1A0J0G	10.00mm



RECOMMENDED P.C.B LAYOUT
TOP VIEW

Material:

- Item ① Terminal body: steel stamping clamp Zinc plating
- Item ② Terminal screw: Steel Zinc plating "-" slot type
- Item ③ Contacts: Brass, Tin plated
- Item ④ Firm wire chunk: steel Zinc plating
- Item ⑤ Terminal housing: Thermoplastic (UL94V-0)
- Item ⑥ Terminal cover: Thermoplastic (UL94V-0)
- Item ⑦ padding block: Thermoplastic (UL94V-0)

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 20A
- Wire range:
- Solid wire(AWG): 12-22
- Stranded wire(AWG): 12-22
- Torque(Lb-In): 2.4
- Screw: M2.5
- Wire strip length: 10-11mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval: 

PART NO.: TR xx 1 5 x 1 A 0J0 G

N=Number of Poles
Dim L=Nx10.0-2.5
Dim P=(N-1)x10.0

Poles	2P-4P	5P-8P	9P-12P
Dim L	±0.20	±0.30	±0.40
Dim P	±0.20	±0.25	±0.30

End stackable
No. of poles
02 2 poles
03 3 poles
...
12 12 poles

Body Color
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
9 White(RAL1102)
C Green(RAL6018/U)

RoHS compliant
(lead<4%)
In copper Alloy

mat'l. code				surface ASME Y14.5	tolerance ASME Y14.5	projection 	product family	
ltr	ecn	no	dr	date	tolerances unless otherwise specified	MM	TERMINAL BLOCK	
					angles X±0.5		TERMINAL BLOCK	
					X.X±0.3		WIRE PROTECTOR,90D WIRE INLET	
					X*±1°	scale	dwg no	
					dr EVIN ZHONG 040114		sheet 1 of 1 size	
					enrg EVIN ZHONG 040114		TRxx15x1A0J0G	
					chr HANKE FENG 040114		A4	
					appd SHI JUN 040114		CUSTOMER Drawing	
sheet index	revision	A						