

Software - VISU+ 2 RT-D 512 - 2988722

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Runtime license for Visu+ where the I/O data and variables in scripting are limited to 512 bytes. 2 direct driver connections are also supported.

Product Features

- Full SCADA (Supervisory Control And Data Acquisition) function with visualization, trend representation, and alarm management
- Control coupling with OPC and 2 direct drivers
- Direct driver connection to controllers, e.g., to Siemens S7 or via Modbus/TCP and Modbus/RTU
- Data logging, trend display, and recipe management
- Scripts can be created in VBA and IL
- Fully scalable process diagrams for using one design on different devices and monitor sizes
- Multilingual software and projects, thanks to Unicode support and online selection
- Access protection with user management



Key Commercial Data

| | |
|----------------------|----------|
| Packing unit | 1 pc |
| Custom tariff number | 85234925 |
| Country of origin | Germany |

Technical data

License information

| | |
|------------------|-----------------|
| Type of software | Visualization |
| Type of license | Runtime license |

Functions

| | |
|---------------------|--|
| Number of I/O nodes | 512 I/O bytes |
| Basic functions | Know-How protection and safety through encoding of projects |
| | Realtime database coupling with ODBC to MS ACCESS, MS EXCEL and SQL server |

Software - VISU+ 2 RT-D 512 - 2988722

Technical data

Functions

| | |
|------------------------|---|
| | FDA CFR 21 Part 11 compatible |
| Expanded functionality | Statistical alarm function |
| | Web client capability |
| | Redundancy function |
| | Advanced alarm management with SMS, FAX, e-mail and voice mail function |
| | Networking |
| | Visu+ as OPC server (DA & XL) |

Hardware requirements

| | |
|---------------------|----------------------------------|
| Hard disk | min. 1 GByte (recommended: 2 GB) |
| CPU | Pentium/Celeron, 1.6 GHz |
| Optical drive | DVD-ROM |
| Monitor resolution | XGA (1024 x 768) |
| Operating equipment | Keyboard, mouse |

Software requirements

| | |
|--------------------|---|
| Operating systems | Windows® XP (SP3) |
| | Windows® Vista Business |
| | Windows® 7 Professional SP1 (32-Bit/64-Bit) |
| | Windows® 7 Ultimate SP1 (32-Bit/64-Bit) |
| | Windows® 8 Professional (32-Bit/64-Bit) |
| | Windows® 8 Enterprise (32-Bit/64-Bit) |
| | Windows® Server 2003 |
| | Windows® Server 2008 |
| | Windows® Server 2008 R2 |
| | Windows® 10 (32-Bit/64-Bit) |
| Supported browsers | Internet Explorer 5.5 or higher |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27248002 |
| eCl@ss 4.1 | 27248002 |
| eCl@ss 5.0 | 27242502 |
| eCl@ss 5.1 | 27242502 |
| eCl@ss 6.0 | 27242502 |

Software - VISU+ 2 RT-D 512 - 2988722

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 7.0 | 27242502 |
| eCl@ss 8.0 | 27242502 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001416 |
| ETIM 3.0 | EC001416 |
| ETIM 4.0 | EC001416 |
| ETIM 5.0 | EC001416 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43163005 |
| UNSPSC 7.0901 | 43232404 |
| UNSPSC 11 | 43163005 |
| UNSPSC 12.01 | 43232404 |
| UNSPSC 13.2 | 43232404 |