












Max. Temperature: 260° during 10 seconds.


0955 355 3611 741	1	M3	Black insulator	Reel Packaging: 140 connectors (See details on page2/2)				
0955 355 3612 741	1	4-40 UNC						
0955 355 6611 741	2	M3						
0955 355 6612 741	2	4-40 UNC						
0955 355 7611 741	3	M3						
0955 355 7612 741	3	4-40 UNC						
Part number	PL	Nut	Index designation					
 All Dimensions in mm Original Size DIN A 3			Techn. Character.		Free size tolerances			
				Dat.	Name	Scale 2 : 1	D-Sub SMT, 25 poles Female, Straight with nuts and ground pins	
			Detail.	25-Oct-11	Johnson.S			
			Insp.	17-Nov-11	Steven.W			
			Stand.	17-Nov-11	Steven.W			
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited				TB 09 55 355 x61x	Page 1 / 2
Mod.	Dat.	Name					Sub.	



Detail A



Detail A



See TB 09 55 355 x61x folio 1/2
for connector dimensions
and PCB layout

Packaging in accordance with
EIA 481-2.

0955 355 3611 741	1	M3	Black insulator	Reel Packaging: 140 connectors
0955 355 3612 741	1	4-40 UNC		
0955 355 6611 741	2	M3		
0955 355 6612 741	2	4-40 UNC		
0955 355 7611 741	3	M3		
0955 355 7612 741	3	4-40 UNC	Index designation	
Part number	PL	Nut		

			All Dimensions in mm Original Size DIN A 3			Techn. Character.			Free size tolerances		
				Dat.	Name	Scale	D-Sub SMT, 25 poles Female, Straight with nuts and ground pins				
			Detail.	25-Oct-11	Johnson.S						
			Insp.	17-Nov-11	Steven.W						
			Stand.	17-Nov-11	Steven.W						
							TB 09 55 355 x61x			Page 2 / 2	
EC04070	17-Nov-11	Johnson.S	Zhuhai HARTING Limited				Sub.				
Mod.	Dat.	Name									