

Front panel feed-through - RC-17S1N8AB0L8 - 1602205

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through of front wall, straight, shielded: yes, Screw locking, M23, No. of pos.: 17, type of contact: Socket, Crimp connection, Flat gasket, 4x Ø2,7, Panel thickness min.: 3 mm, Panel thickness max.: 7 mm, cable diameter range: 6.5 mm ... 7.5 mm



Key Commercial Data

Packing unit	20 pc
GTIN	 4 046356 238601
GTIN	4046356238601


Technical data

Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Schematic diagram




Dimensional drawing



Front panel feed-through - RC-17S1N8AB0L8 - 1602205

Dimensional drawing



Installation dimensions
Flat gasket, radial O-ring

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>