


## 59045 Mini PCB Mount Features and Benefits



### Features

- 2 part magnetically operated proximity sensor
- Normally open contact configuration
- Moulded stand-offs to allow board washing
- Customer defined sensitivity


### Benefits

- Mounts directly into printed circuit board
- No standby power requirement
- Operates through non-ferrous materials such as wood, plastic or aluminium
- Hermetically sealed, magnetically operated contacts continue to operate long after optical and other technologies fail due to contamination
- Simple installation and adjustment

### Applications

- Position and limit sensing
- Security system switch
- Door switch

## DIMENSIONS (in) mm



	A Max	B Max	C ± .10 (0,25)	D Max	E ± .015 (0,38)
57045	(.170) 4,32	(.700) 17,78	See Note Below	(.130) 3,3	—
59045	(.170) 4,32	(.700) 17,78	(.600) 15,24	(.130) 3,3	(.130) 3,30

Mounting: (.062) 1.57 thick board, (.125) 3.17 holes on (.540) 13.72

## CUSTOMER OPTIONS - Switching Specifications

TABLE 1 Contact Type			Normally Open
Switch Type			I
Power	Switching	Watt - max.	10
	Breakdown	Vdc - max.	200
Voltage	Switching	Vdc - min.	250
	Carry	A - max.	0.5
Current	Contact, Initial	Ω - max.	0.2
	Insulation	Ω - min.	10 <sup>10</sup>
Resistance	Contact	pF - typ.	0.3
Capacitance	Operating	°C	-40 to +105
	Storage	°C	-65 to +105
Temperature	Operate	ms - max.	1.0
	Release	ms - max.	1.0
Time	Shock	11ms 1/2 sine	G - max.
Shock	Vibration	50-2000 Hz	G - max.
Vibration			30

## CUSTOMER OPTIONS - Sensitivity

TABLE 2

**Sensitivity Options:-**  
Activate Distances are approximate using Hamlin 57045 actuator as illustrated  
Switch AT before modification



Switch Type	Select Option	S		T		U	
		Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm
I	Normally Open	15-20	(.197) 5,0	20-25	(.177) 4,5	25-30	(.157) 4,0

## ORDERING INFORMATION

59045 - I - X - 00 - 0

Series 59045

Switch Type

Sensitivity

— Table 1

— Table 2

Hamlin USA Tel: +1 920 648 3000 • Fax: +1 920 648 3001 • Email: sales.us@hamlin.com  
 Hamlin UK Tel: +44 (0)1379 649700 • Fax: +44 (0)1379 649702 • Email: sales.uk@hamlin.com  
 Hamlin Germany Tel: +49 (0) 6181 953660 • Fax: +49 (0) 6181 9536666 • Email: sales.de@hamlin.com  
 Hamletrol France Tel: +33 (0) 1 4687 0202 • Fax: +33 (0) 1 4686 6786 • Email: sales.fr@hamlin.com