


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF20292-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	1820 @ 0°C	810	5	38,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP							
A DIMENSION CHANGES RELEASED			DRAWN BY L. WENGSTROM		APP'VD BY DATE F.D. 12/19/02		SIZE A		FSCM NO. 55335		DRAWING NO. BF20292-24B	
REV. NO. DESCRIPTION/ECO NUMBER			APP'VD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 2/28/02		REVISION DATE 12/19/02	
							REV. NO. A		SHEET 1 OF 1			