

Fuse Blocks, 5 x 20 and 5 x 25 mm


Altech fuse terminals are also available with light indication - CF4U(L). A specially designed built-in circuit gives light indication in the event of fuse blow out. Thus, fault in a circuit can be easily located. No polarity is required.

Important:

The disconnecting device is not suitable for interrupting load. The supply must be switched off before operating the slide link/lever.

† Fuses are sold separately see pages 100-101.

* Add required voltage to part number as a suffix. i.e. CF4U(L)/6-60 for 6-60 V AC/DC.



| | | | | | | | | | | | | | | | | |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------------|-----------------|-----------|-----------------------|-----------|-------|--------|-------|------|-------|------|---------|--------|---------|
| Terminal Width | 8 mm | | | | | | | | | | | | | | | |
| Height x Length | 57.6 x 57 mm | | | | | | | | | | | | | | | |
| Stripping Length | 9.5 mm | | | | | | | | | | | | | | | |
| Insulation Material | Polyamide 6.6 | | | | | | | | | | | | | | | |
| Type of Connection | 2 screw clamps | | | | | | | | | | | | | | | |
| LED Voltage | 6-60 V AC/DC 90-240 V AC/DC | | | | | | | | | | | | | | | |
| Size of Fuse Used | Ø5x20, Ø5x25 mm | | | | | | | | | | | | | | | |
| Type of Fuse Used | Glass | | | | | | | | | | | | | | | |
| Approvals | <table border="1"> <tr><td>SA C US</td><td>IEC 60947-7-3</td><td>FU C US E220514</td></tr> <tr><td>22-10 AWG</td><td>0.2-4 mm²</td><td>22-10 AWG</td></tr> <tr><td>600 V</td><td>1000 V</td><td>600 V</td></tr> <tr><td>10 A</td><td>6.3 A</td><td>10 A</td></tr> <tr><td>7 lb-in</td><td>0.5 Nm</td><td>7 lb-in</td></tr> </table> | SA C US | IEC 60947-7-3 | FU C US E220514 | 22-10 AWG | 0.2-4 mm ² | 22-10 AWG | 600 V | 1000 V | 600 V | 10 A | 6.3 A | 10 A | 7 lb-in | 0.5 Nm | 7 lb-in |
| SA C US | IEC 60947-7-3 | FU C US E220514 | | | | | | | | | | | | | | |
| 22-10 AWG | 0.2-4 mm ² | 22-10 AWG | | | | | | | | | | | | | | |
| 600 V | 1000 V | 600 V | | | | | | | | | | | | | | |
| 10 A | 6.3 A | 10 A | | | | | | | | | | | | | | |
| 7 lb-in | 0.5 Nm | 7 lb-in | | | | | | | | | | | | | | |
| Wire Range | | | | | | | | | | | | | | | | |
| Voltage Rating | | | | | | | | | | | | | | | | |
| Current Rating | | | | | | | | | | | | | | | | |
| Torque | | | | | | | | | | | | | | | | |
| Other Approvals | | | | | | | | | | | | | | | | |

Terminal Block

DIN Rail for ordering information refer to pages 90-91

End Stop for ordering information refer to page 92

| | | |
|-----------------|---------|--|
| Internal Jumper | 2 pole | |
| | 3 pole | |
| | 4 pole | |
| | 10 pole | |

| | | |
|---------------------------|---------|--|
| Insulated Internal Jumper | 2 pole | |
| | 3 pole | |
| | 4 pole | |
| | 10 pole | |

| | | |
|-------------|---------|--|
| Current Bar | 2 pole | |
| | 3 pole | |
| | 4 pole | |
| | 10 pole | |

Shorting Sleeve & Screw


| | | |
|-----------------|---------|--|
| External Jumper | 2 pole | |
| | 3 pole | |
| | 4 pole | |
| | 10 pole | |

Marking Tags (on terminal)

(on Lever)

| COLOR BLOCKS | | |
|---------------------------------------------------|-----------------|--|
| (other than standard grey) | | |
| When ordering please add color suffix to Cat. No. | | |
| Example for color Red: Cat.No./R | | |
| Color | Ordering Suffix | |
| Red | R | |
| Yellow | Y | |
| Blue | BU | |
| Green | G | |
| Consult Altech for availability: | | |
| Orange | O | |
| Beige | BG | |
| Dark Brown | DB | |
| Black | BL | |
| White | W | |

CF4U†




No End Plate Required.

| | | | | | | | | | | | | | | | | |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------------|-----------------|-----------|-----------------------|-----------|-------|--------|-------|------|-------|------|---------|--------|---------|
| Terminal Width | 8 mm | | | | | | | | | | | | | | | |
| Height x Length | 57.6 x 57 mm | | | | | | | | | | | | | | | |
| Stripping Length | 9.5 mm | | | | | | | | | | | | | | | |
| Insulation Material | Polyamide 6.6 | | | | | | | | | | | | | | | |
| Type of Connection | 2 screw clamps | | | | | | | | | | | | | | | |
| LED Voltage | | | | | | | | | | | | | | | | |
| Size of Fuse Used | Ø5x20, Ø5x25 mm | | | | | | | | | | | | | | | |
| Type of Fuse Used | Glass | | | | | | | | | | | | | | | |
| Approvals | <table border="1"> <tr><td>SA C US</td><td>IEC 60947-7-3</td><td>FU C US E220514</td></tr> <tr><td>22-10 AWG</td><td>0.2-4 mm²</td><td>22-10 AWG</td></tr> <tr><td>600 V</td><td>1000 V</td><td>600 V</td></tr> <tr><td>10 A</td><td>6.3 A</td><td>10 A</td></tr> <tr><td>7 lb-in</td><td>0.5 Nm</td><td>7 lb-in</td></tr> </table> | SA C US | IEC 60947-7-3 | FU C US E220514 | 22-10 AWG | 0.2-4 mm ² | 22-10 AWG | 600 V | 1000 V | 600 V | 10 A | 6.3 A | 10 A | 7 lb-in | 0.5 Nm | 7 lb-in |
| SA C US | IEC 60947-7-3 | FU C US E220514 | | | | | | | | | | | | | | |
| 22-10 AWG | 0.2-4 mm ² | 22-10 AWG | | | | | | | | | | | | | | |
| 600 V | 1000 V | 600 V | | | | | | | | | | | | | | |
| 10 A | 6.3 A | 10 A | | | | | | | | | | | | | | |
| 7 lb-in | 0.5 Nm | 7 lb-in | | | | | | | | | | | | | | |
| Wire Range | | | | | | | | | | | | | | | | |
| Voltage Rating | | | | | | | | | | | | | | | | |
| Current Rating | | | | | | | | | | | | | | | | |
| Torque | | | | | | | | | | | | | | | | |
| Other Approvals | | | | | | | | | | | | | | | | |



| Cat. No. | Std. Pk. |
|----------|----------|
|----------|----------|

CF4U 100




| | |
|-------|----|
| CA702 | 50 |
| CA802 | 50 |

| | |
|----------|-----|
| CA711/2 | 100 |
| CA711/3 | 50 |
| CA711/4 | 50 |
| CA711/10 | 20 |

MT8 100
MT8 100

CF4U(L)†*




No Polarity Required.

| | | | | | | | | | | | | | | | | |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------------|-----------------|-----------|-----------------------|-----------|-------|-------|-------|------|-------|------|---------|--------|---------|
| Terminal Width | 8 mm | | | | | | | | | | | | | | | |
| Height x Length | 57.6 x 57 mm | | | | | | | | | | | | | | | |
| Stripping Length | 9.5 mm | | | | | | | | | | | | | | | |
| Insulation Material | Polyamide 6.6 | | | | | | | | | | | | | | | |
| Type of Connection | 2 screw clamps | | | | | | | | | | | | | | | |
| LED Voltage | CF4U(L)/6-60V CF4U(L)/90-240V | | | | | | | | | | | | | | | |
| Size of Fuse Used | Ø5x20, Ø5x25 mm | | | | | | | | | | | | | | | |
| Type of Fuse Used | Glass | | | | | | | | | | | | | | | |
| Approvals | <table border="1"> <tr><td>SA C US</td><td>IEC 60947-7-3</td><td>FU C US E220514</td></tr> <tr><td>22-10 AWG</td><td>0.2-4 mm²</td><td>22-10 AWG</td></tr> <tr><td>600 V</td><td>600 V</td><td>600 V</td></tr> <tr><td>10 A</td><td>6.3 A</td><td>10 A</td></tr> <tr><td>7 lb-in</td><td>0.5 Nm</td><td>7 lb-in</td></tr> </table> | SA C US | IEC 60947-7-3 | FU C US E220514 | 22-10 AWG | 0.2-4 mm ² | 22-10 AWG | 600 V | 600 V | 600 V | 10 A | 6.3 A | 10 A | 7 lb-in | 0.5 Nm | 7 lb-in |
| SA C US | IEC 60947-7-3 | FU C US E220514 | | | | | | | | | | | | | | |
| 22-10 AWG | 0.2-4 mm ² | 22-10 AWG | | | | | | | | | | | | | | |
| 600 V | 600 V | 600 V | | | | | | | | | | | | | | |
| 10 A | 6.3 A | 10 A | | | | | | | | | | | | | | |
| 7 lb-in | 0.5 Nm | 7 lb-in | | | | | | | | | | | | | | |
| Wire Range | | | | | | | | | | | | | | | | |
| Voltage Rating | | | | | | | | | | | | | | | | |
| Current Rating | | | | | | | | | | | | | | | | |
| Torque | | | | | | | | | | | | | | | | |
| Other Approvals | | | | | | | | | | | | | | | | |



| Cat. No. | Std. Pk. |
|----------|----------|
|----------|----------|

CF4U(L)* 50



| | |
|-------|----|
| CA702 | 50 |
| CA802 | 50 |

| | |
|----------|-----|
| CA711/2 | 100 |
| CA711/3 | 50 |
| CA711/4 | 50 |
| CA711/10 | 25 |

MT8 100
MT8 100

